claire

SAFETY DATA SHEET

1. Identification

Product number 301

Product identifier Fast Kill Residual Roach & Ant Killer

Revision date 06-16-2014

Company information Claire Manufacturing Co.

1005 Westgate Drive

Addison, IL 60101 United States

Company phone 630-543-7600

Version # 02

Supersedes date06-16-2014Recommended useNot available.Recommended restrictionsNone known.

2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 1Health hazardsSensitization, skinCategory 1Aspiration hazardCategory 1

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. May be fatal if swallowed and enters airways. May cause an allergic

skin reaction.

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Contaminated work clothing must not be allowed out of the workplace. Wear

protective gloves.

Response If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water.

Specific treatment (see this label). Do NOT induce vomiting. If skin irritation or rash occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

Storage Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

Not classified.

Environmental hazards Hazardous to the aquatic environment, acute Category 1

hazard

Hazardous to the aquatic environment, Category 1

long-term hazard

Supplemental information

Hazard statement Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Prevention Avoid release to the environment.

Response Collect spillage.

Not applicable.

3. Composition/information on ingredients

Mixtures

Hazardous components

Chemical nameCommon name and synonymsCAS number%Distillates (Petroleum),
Hydrotreated Light64742-47-880 - 90

Product name: 15 OZ DOOM RESIDUAL ROACH&ANT KLR LB 6PK

Product #: 1000012030 Version #: 02 Revision date: 06-16-2014 Issue date: 06-16-2014 1

Hazardous components Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	2.5 - 10
Propane		74-98-6	2.5 - 10
Esfenvalerate		66230-04-4	0.1 - 1

^{#:} This substance has workplace exposure limit(s).

4. First-aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if

victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped

with a one-way valve or other proper respiratory medical device. Get medical attention

immediately.

Skin contact Take off immediately all contaminated clothing. Wash off with warm water and soap. If skin

irritation or rash occurs: Get medical advice/attention. For minor skin contact, avoid spreading

material on unaffected skin.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs,

keep head low so that stomach content doesn't get into the lungs. Aspiration may cause

pulmonary edema and pneumonitis. No need for first aid is anticipated if material is swallowed.

Most important symptoms/effects, acute and

May cause allergic skin reaction.

delayed

Indication of immediate medical attention and special Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

treatment needed **General information**

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Immediate medical attention is required. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Ingestion

Powder. Alcohol resistant foam. Dry chemicals. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters Contents under pressure. Pressurized container may explode when exposed to heat or flame. Fire may produce irritating, corrosive and/or toxic gases.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear full protective clothing including self contained breathing apparatus.

Fire-fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. In the event of fire and/or explosion do not breathe fumes.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Consider initial downwind evacuation for at least 500 meters (1/3 mile). Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Pay attention to flashback. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid breathing gas. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the MSDS.

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Keep out of low areas. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Collect spillage. Use water spray to reduce vapors or divert vapor cloud drift. Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination. This material and its container must be disposed of as hazardous waste. For waste disposal, see section 13 of the MSDS.

Environmental precautions

Avoid release to the environment. Refer to special instructions/safety data sheets. Contact local authorities in case of spillage to drain/aquatic environment. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Vapors may form explosive mixtures with air. May be ignited by open flame. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin. Avoid contact with eyes. Avoid

prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in area provided with appropriate exhaust ventilation. Observe good industrial hygiene practices. Wash hands thoroughly after handling. Handle and open container with care. Use appropriate container to avoid

environmental contamination. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks, and flame. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. The pressure in sealed containers can increase under the influence of heat. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Use appropriate container to avoid environmental contamination. Store in a well-ventilated place. Keep away from food, drink and animal feedingstuffs. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the MSDS). Level 3 Aerosol.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
US. NIOSH: Pocket Guide	to Chemical Hazards		
Components	Type	Value	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
, ,		1000 ppm	
logical limit values	No biological exposure limits noted for the ingredient(s).		
osure guidelines	No Exposure standards allocated.		
ropriate engineering trols	Ensure adequate ventilation, especi	ally in confined areas.	

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear protective gloves.

Other Wear appropriate chemical resistant clothing. Chemical resistant gloves.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid contact with skin. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

Product name: 15 OZ DOOM RESIDUAL ROACH&ANT KLR LB 6PK

Product #: 1000012030 Version #: 02 Revision date: 06-16-2014 Issue date: 06-16-2014

9. Physical and chemical properties

Appearance Compressed liquefied gas.

Color clear colorless **Form** Aerosol. Physical state Gas.

Boiling point 356 °F (180 °C) estimated

Flash point -156.00 °F (-104.44 °C) Propellant estimated

Not available. Melting point/freezing point Odor Solvent.

Not applicable estimated pН

Solubility(ies) Not available. Not available. Vapor density

Vapor pressure 35 - 50 psig @70F estimated

Not available. **Viscosity**

Other information

Specific gravity 0.765 estimated estimated

10. Stability and reactivity

Reactivity Strong oxidizing agents.

Chemical stability Risk of ignition.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Aerosol containers are unstable at temperatures above 49°C. Avoid

temperatures exceeding the flash point.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

May be fatal if swallowed and enters airways. Ingestion Inhalation May be fatal if swallowed and enters airways.

Skin contact May cause an allergic skin reaction.

Direct contact with eyes may cause temporary irritation. Eye contact Symptoms related to the Direct contact with eyes may cause temporary irritation.

physical, chemical and toxicological characteristics

Information on toxicological effects

Acute toxicity Acute LD50: 2356 mg/kg, Rat, Dermal

May be fatal if swallowed and enters airways. May cause allergic skin reaction.

Product Species Test Results

15 OZ DOOM RESIDUAL ROACH&ANT KLR LB 6PK (CAS Mixture)

Acute

Dermal

LD50 Rat 2356 mg/kg

Inhalation

LC50 Mouse 9444.4443 mg/l, 2 Hours, estimated

> Rat 18498.0391 mg/l, 15 Minutes, estimated

> > 456.1718 mg/l, 4 Hours, estimated

6 mg/l/4h

Oral

LD50 Rat

Product name: 15 OZ DOOM RESIDUAL ROACH&ANT KLR LB 6PK

Components	Species	Test Results
Butane (CAS 106-97-8)		
Acute		
Inhalation		
LC50	Mouse	680 mg/l, 2 Hours
	Rat	658 mg/l, 4 Hours
Esfenvalerate (CAS 66230-	04-4)	
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
	Rat	> 5000 mg/kg
Inhalation		
LC50	Rat	0.48 mg/l, 4 Hours
Oral		
LD50	Mouse	250 mg/kg
	Rat	88 mg/kg
Propane (CAS 74-98-6)		
Acute		
Inhalation		
LC50	Rat	> 1442.847 mg/l, 15 Minutes
		658 mg/l/4h
		3

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Not expected to be hazardous by OSHA criteria.

Serious eye damage/eye

Respiratory sensitization

irritation

tion

Irritating to eyes.

Not available.

Skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Not expected to be hazardous by OSHA criteria.

Carcinogenicity

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Reproductive toxicity

Not expected to be hazardous by OSHA criteria.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Fish

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects

Hazardous by OSHA criteria. Repeated absorption may cause disorder of central nervous system,

liver, kidneys and blood. Prolonged exposure may cause chronic effects.

Further information Symptoms may be delayed. This product has no known adverse effect on human health.

12. Ecological information

Ecotoxicity LC50: 53 mg/L, Fish, 96.00 Hours

Very toxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Fathead minnow (Pimephales promelas) 0.0002 - 0.0003 mg/l, 96 hours

Product		Species	Test Results
15 OZ DOOM RESID	UAL ROACH&ANT	KLR LB 6PK (CAS Mixture)	
Fish	LC50	Fish	53.0035 mg/L, 96 Hours
Components		Species	Test Results
Distillates (Petroleum	n), Hydrotreated Ligh	nt (CAS 64742-47-8)	
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
Esfenvalerate (CAS 6	66230-04-4)		
Aquatic			

^{*} Estimates for product may be based on additional component data not shown.

LC50

Persistence and degradability
No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Propane 2.36 Butane 2.89

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. If discarded, this product is considered a RCRA ignitable waste, D001. After recovery of solvent dispose of residue as hazardous waste. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es) 2.1

Subsidiary class(es) Not available.

Packing group Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Labels requiredNoneSpecial provisionsN82Packaging exceptions306Packaging non bulkNonePackaging bulkNone

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es) 2.1 Subsidiary class(es) -

Packaging group Not available.

Environmental hazards Yes
Labels required 2.1
ERG Code 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions LTD QTY

IMDG

UN number UN1950

UN proper shipping name AEROSOLS, MARINE POLLUTANT

Transport hazard class(es) 2.1 Subsidiary class(es) -

Packaging group Not available.

Environmental hazards

Marine pollutantYesLabels required2.1EmSF-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions

LTD QTY

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

DOT



IATA; IMDG



Marine pollutant



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

SARA 304 Emergency release notification

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely

hazardous substance

No

SARA 311/312 Hazardous

No

chemical

Product name: 15 OZ DOOM RESIDUAL ROACH&ANT KLR LB 6PK

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Not listed.

Food and Drug

Not regulated.

Administration (FDA)

US state regulationsThis product does not contain a chemical known to the State of California to cause cancer, birth

defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8) 500 lbs Propane (CAS 74-98-6) 500 lbs

Inventory name

US. Pennsylvania RTK - Hazardous Substances

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

 Issue date
 06-16-2014

 Revision date
 06-16-2014

Version # 02

United States & Puerto Rico

Further information Not available.

Disclaimer The information in the sheet was written based on the best knowledge and experience currently

available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with

any other materials or in any process, unless specified in the text.

Revision Information Physical & Chemical Properties: Multiple Properties

Transport information: Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Regulatory Information: United States

GHS: Classification

Product name: 15 OZ DOOM RESIDUAL ROACH&ANT KLR LB 6PK

Product #: 1000012030 Version #: 02 Revision date: 06-16-2014 Issue date: 06-16-2014 8

Yes

On inventory (yes/no)*

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).