HILLYARD The Cleaning Resource

SAFETY DATA SHEET

1. Identification

Product identifier TACK-IT

Other means of identification

SDS number 590N-100A
Product code HIL00458
Recommended use Floor Cleaner

Recommended restrictions For Labeled Use Only **Manufacturer/Importer/Supplier/Distributor information**

Manufacturer

Company name HILLYARD INDUSTRIES

Address 302 North Fourth St.

St. Joseph, MO 64501

Contact person Regulatory Affairs

Telephone number (800) 365-1555 (Ext. 8206)

Fax (816) 383-8406

E-mail regulatoryaffairs@hillyard.com

Emergency telephone # (800) 424-9300

(Only in the event of chemical emergency involving a spill, leak, fire, exposure or accident

involving chemicals)

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 4Health hazardsAcute toxicity, oralCategory 5Acute toxicity, inhalationCategory 5

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Hazard symbol None.

Signal word Warning

Hazard statement Combustible liquid. May be harmful if swallowed. May be harmful if inhaled.

Precautionary statement

Prevention Keep away from flames and hot surfaces. No smoking. Wear protective gloves/eye

protection/face protection. Avoid contact with eyes.

Response IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a poison center/doctor if you feel unwell. IF SWALLOWED: Call a

POISON CENTER or doctor/physician if you feel unwell.

Storage Store in a well-ventilated place. Keep cool.

Disposal Buyer assumes all risk and liability associated with disposal of this product (original concentration

or dilution) in violation of applicable law in compliance with applicable federal, state and local requirements. CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer clean, dry

container for recycling or reconditioning.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Butoxyethanol		111-76-2	1 - < 3
Isopropanol		67-63-0	1 - < 3
Other components below re	eportable levels		90 - 100

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center or doctor/physician if you feel unwell.

Direct contact with eyes may cause temporary irritation.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Ingestion Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods General fire hazards Use standard firefighting procedures and consider the hazards of other involved materials.

Combustible liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Keep away from open flames, hot surfaces and sources of ignition. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Avoid inhalation of vapors and spray mists. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Permissible E Components	Exposure Limits (PEL) for Air Type	Contaminants (29 CFR 1910.1000) Value	
Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m3	
		50 ppm	
Isopropanol (CAS 67-63-0)	PEL	980 mg/m3	
		400 ppm	
US. ACGIH Threshold Limit Value	s (TLV)		
Components	Type	Value	
Butoxyethanol (CAS 111-76-2)	TWA	20 ppm	
Isopropanol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
NIOSH. Immediately Dangerous to	Life or Health (IDLH) Values	, as amended	
Components	Type	Value	
Butoxyethanol (CAS 111-76-2)	IDLH	1.1 %	
		700 ppm	
Isopropanol (CAS 67-63-0)	IDLH	2 %	
		2000 ppm	
US. NIOSH: Pocket Guide to Chem		•	
Components	Туре	Value	
Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m3	
		5 ppm	
Isopropanol (CAS 67-63-0)	STEL	1225 mg/m3	
		500 ppm	
	TWA	980 mg/m3	
		400 ppm	

Biological limit values

ACGIH Biological Exposure Indices (BEI)

Components	Value ` ´	Determinant	Specimen	Sampling Time	
Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*	
Isopropanol (CAS 67-63-0) 40 mg/l	Acetone	Urine	*	

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Butoxyethanol (CAS 111-76-2) Skin designation applies.

US - Tennessee OELs: Skin designation

Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been

established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes. Where splashing of concentrate is a concern, use protective glasses with

side shield

Skin protection

Hand protection For prolonged or repeated skin contact use suitable protective gloves.

Other Wear suitable protective clothing. None normally required. If unable to avoid prolonged or

repeated contact with skin, wear impervious clothing.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards None known.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Clear, colorless liquid

Physical state Liquid.
Form Liquid.
Color Colorless
Odor Mild IPA
Odor threshold Not available

pH 6 - 8

Melting point/freezing point Not applicable / Not available

Initial boiling point and boiling

range

208 °F (97.78 °C)

Flash point >141.0 °F (>60.6 °C) Tag Closed Cup

Evaporation rate <1 (ethyl ether = 1) **Flammability (solid, gas)** Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.
Explosive limit - upper (%) Not available.

Vapor pressure 17.61 mm Hg

Vapor density 0.7118 AIR=1

Relative density 0.99 at 77°F

Solubility(ies)

Solubility (water) 100 % Complete
Partition coefficient Not available

(n-octanol/water)

Auto-ignition temperature Not available

Decomposition temperature Not available

Viscosity Not available

Other information

Density 8.28

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Percent volatile >99 % VOC 4 %

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials

Hazardous decomposition

products

Strong oxidizing agents.

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May be harmful if inhaled.

Butoxyethanol may be absorbed through the skin in toxic amounts if contact is repeated and Skin contact

prolonged. These effects have not been observed in humans.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

Eye contact Direct contact with eyes may cause temporary irritation.

May be harmful if swallowed. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

May be harmful if inhaled. May be harmful if swallowed. **Acute toxicity**

Product **Species Test Results**

TACK-IT

Acute

Dermal

LD50 Rabbit 23881 mg/kg Components **Species Test Results**

Butoxyethanol (CAS 111-76-2)

Acute

Oral

LD50 Rat 470 mg/kg

Isopropanol (CAS 67-63-0)

Acute

Dermal

LD50 Rabbit 12800 mg/kg

Inhalation

LC50 Rat 51.05 mg/l, 8 Hours

Oral

LD50 Rat 4710 mg/kg

Prolonged skin contact may cause temporary irritation. Skin corrosion/irritation

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Not classifiable as to carcinogenicity to humans. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Butoxyethanol (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Prolonged inhalation may be harmful.

Chronic effects

Prolonged inhalation may be harmful. May be harmful if absorbed through skin.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product		Species	Test Results
TACK-IT			
Aquatic			
Crustacea	EC50	Daphnia	13680.2988 mg/l, 48 hours estimated
Fish	LC50	Fish	230956848 mg/l, 96 hours estimated
Acute			
Crustacea	EC50	Daphnia	6472.6309 mg/l, 48 hours estimated
Fish	LC50	Fish	33396.9453 mg/l, 96 hours estimated
Components		Species	Test Results
Butoxyethanol (CAS	111-76-2)		
Aquatic			
Acute			
Fish	LC50	Inland silverside (Menidia beryllina)	1250 mg/l, 96 hours
Isopropanol (CAS 67-	-63-0)		
Aquatic			

Fish Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Acute

Partition coefficient n-octanol / water (log Kow)

Butoxyethanol 0.83 0.05 Isopropanol

LC50

Mobility in soil This product is completely water soluble and will disperse in soil.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Western mosquitofish (Gambusia affinis) > 1400 mg/l, 96 hours

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

UN number UN1993

UN proper shipping name Flammable liquid, n.o.s. (Isopropyl Alcohol)

Transport hazard class(es)

Class 3 Subsidiary hazard -

Label(s) Flammable

Packing group III Environmental hazards No. ERG Code 128

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1993

UN proper shipping name FLAMMABLE LIQUID, N.O.S. (Isopropyl Alcohol)

Not established.

Transport hazard class(es)

Class 3
Subsidiary hazard -

Label(s) Flammable

Packing group

Environmental hazards

Marine pollutant No. EmS F-E, S-E

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

IATA; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

One or more components of the mixture are not on the TSCA 8(b) inventory

or are designated "inactive".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Flammable (gases, aerosols, liquids, or solids)

categories Acute toxicity (any route of exposure)

SARA 313 (TRI reporting)

Classified hazard

 Chemical name
 CAS number
 % by wt.

 Isopropanol
 67-63-0
 1 - < 3</td>

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Isopropanol (CAS 67-63-0)

Low priority

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Butoxyethanol (CAS 111-76-2) Isopropanol (CAS 67-63-0)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or regionInventory nameOn inventory (yes/no)*CanadaDomestic Substances List (DSL)YesCanadaNon-Domestic Substances List (NDSL)NoUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryYes

16. Other information, including date of preparation or last revision

 Issue date
 11-24-2014

 Revision date
 04-22-2024

Version # 04

HMIS® ratings Health: 1

Flammability: 2 Physical hazard: 0

DisclaimerNo representations or warranties, either express or implied, of merchantability, fitness for a

particular purpose, or of any nature are made with respect to the product(s) or information contained in this material safety data sheet. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. The buyer or user assumes all risks associated with the use, misuse or disposal of this product. The buyer or user is responsible to comply with all federal, state or local regulations concerning the use, misuse or

disposal of these products.

Revision informationThis document has undergone significant changes and should be reviewed in its entirety.

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).