MATERIAL SAFETY DATA SHEET comply with OSHA's Hazard C	(SUBSTITUTES	FOR OSHA F	ORM 174): M	ay be used to
PRODUCT NUMBER: 249 IDENTITY: BRILLIANCE	Revision Date: 01/24/2007			
Section I				
Manufacturer's Name:QUEST CHEMICAL CORPORATION Address: 12255 FM 529 NORTHWOODS INDUSTRIAL PARK HOUSTON State: TX Zip Code:77041			Telephone Numbers: Emergency: 800/255-3924 Information: 713/8968188	
HMIS CODES: REACTIVITY: 1 F	LAMMABILITY:	2 HEALTH:	1 PERSONA	L PROTECT: A
Section II: HAZARDOUS INGR ingredients contained in th				
Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM %
ISOPARAFINIC HYDROCARBON MINERAL SEAL OIL PROPANE/N-BUTANE	64741-44-2		5 MG/M3	N/A
Section III: PHYSICAL/CHEM	011 0111111011			
Boiling Point: Vapor Pressure(mm Hg) Vapor Density(AIR=1) Solubility in Water: Appearance and Odor: CLEAR	430 Spec <0.1 Melt >1 Evan 0% (But	cific Gravit ting Point: poration Ra tyl Acetate	y (water=1) te:	
Section IV: FIRE AND EXPLO				
Flash Point(Method Used):>1 Extinguishing Media: STANDA Special Fire Fighting Proce WHEN INDICATED	85F TCC Flar RD CHEMICAL I	mmable Limi FIRE EXTING	ts: LEL:N/	A UEL: N/A

Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

PRODUCT NUMBER: 249 ______

Stability: Unstable: Conditions to avoid: TEMPERATURES ABOVE 120 F

Stable: X HOT SURFACES

Incompatability (Materials to Avoid): SOME PLASTICS

Hazardous Decomposition or Byproducts: NONE

Hazardous Polymerization: May Occur: Will Not Occur: X

Conditions to Avoid: NONE

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Health Hazards (Acute and Chronic):

INHALATION: DIZZINESS. EXCESSIVE EXPOSURE MAY LEAD TO UNCONSCIOUSNESS. EYES: IRRITATION, REDDENING. SKIN: MAY CAUSE LOCALIZED DRYNESS IF OVER-EXPOSED.

Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO

Signs and Symptoms of Exposure: SEE HEALTH HAZARDS ABOVE

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. SKIN: IN CASE OF CONTACT, WASH THOROUGHLY WITH SOAP AND WATER. EYES: FLUSH WITH WATER FOR 15 MINUTES. CONTACT PHYSICIAN IF IRRITATION PERSISTS.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG OR USE SOME ABSORBENT CLAY MATERIAL. DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL GUIDELINES.

Waste Disposal Method: DO NOT PUNCTURE OR INCINERATE CONTAINER. DO NOT REUSE CONTAINER. WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT USE OR STORE NEAR HEAT OR OPEN FLAMES. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Other Precautions: NONE

Section VIII: CONTROL MEASURES

Respiratory Protection: N/A

Ventilation: Local Exhaust:ADEQUATE

Mechanical: N/A Special: N/A

Other: N/A Protective Gloves:N/A

Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.

Other Protective Clothing or Equipment:

N/A

Work/Hygienic Practices:

WASH HANDS AFTER USE