

**1. Identification**

**Product identifier** TACK-IT

**Other means of identification**

**SDS number** 573N-12A

**Product code** HIL00458

**Recommended use** Floor Cleaner

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufacturer**

**Manufacturer**

**Company name** HILLYARD INDUSTRIES

**Address** 302 North Fourth St.  
St. Joseph, MO 64501

**Contact person** Regulatory Affairs

**Telephone number** (816) 233-1321 (Ext. 8285)

**Fax** (816) 383-8485

**E-mail** regulatoryaffairs@hillyard.com

**Emergency telephone #** (800) 424-9300  
(Only in the event of chemical emergency involving a spill, leak, fire, exposure, or accident involving chemicals.)

**2. Hazard(s) identification**

**Physical hazards** Flammable liquids Category 4

**Health hazards** Acute toxicity, oral Category 5  
Acute toxicity, inhalation Category 5

**Environmental hazards** Not classified.

**OSHA defined hazards** Not classified.

**Label elements**

**Hazard symbol** None.

**Signal word** Warning

**Hazard statement** Combustible liquid. May be harmful if swallowed. May be harmful if inhaled.

**Precautionary statement**

**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid contact with eyes

**Response** If in eyes, flush with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

**Storage** Store in a well-ventilated place. Keep cool.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)** None known.

**Supplemental information** None.

**3. Composition/information on ingredients**

**Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Ethylene glycol monobutyl ether		111-76-2	1 - < 3
Isopropyl Alcohol		67-63-0	1 - < 3
Other components below reportable levels			90 - 100

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

<b>Inhalation</b>	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
<b>Skin contact</b>	Wash off with soap and water. Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Rinse with water. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.
<b>Most important symptoms/effects, acute and delayed</b>	Direct contact with eyes may cause temporary irritation.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

## 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Combustible liquid.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water.  Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.  Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.  Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Keep away from open flames, hot surfaces and sources of ignition. Do not get in eyes, on skin, or on clothing. Avoid inhalation of vapors and spray mists. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
<b>Conditions for safe storage, including any incompatibilities</b>	Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Ethylene glycol monobutyl ether (CAS 111-76-2)	PEL	240 mg/m <sup>3</sup>
Isopropyl Alcohol (CAS 67-63-0)	PEL	50 ppm 980 mg/m <sup>3</sup>
		400 ppm

#### US. ACGIH Threshold Limit Values

Components	Type	Value
Ethylene glycol monobutyl ether (CAS 111-76-2)	TWA	20 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Ethylene glycol monobutyl ether (CAS 111-76-2)	TWA	24 mg/m <sup>3</sup>
		5 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	1225 mg/m <sup>3</sup>
		500 ppm
	TWA	980 mg/m <sup>3</sup> 400 ppm

### Biological limit values

#### ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Ethylene glycol monobutyl ether (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*
Isopropyl Alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

\* - For sampling details, please see the source document.

### Exposure guidelines

#### US - California OELs: Skin designation

Ethylene glycol monobutyl ether (CAS 111-76-2) Can be absorbed through the skin.

#### US - Minnesota Haz Subs: Skin designation applies

Ethylene glycol monobutyl ether (CAS 111-76-2) Skin designation applies.

#### US - Tennessee OELs: Skin designation

Ethylene glycol monobutyl ether (CAS 111-76-2) Can be absorbed through the skin.

#### US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Ethylene glycol monobutyl ether (CAS 111-76-2) Can be absorbed through the skin.

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Ethylene glycol monobutyl ether (CAS 111-76-2) Can be absorbed through the skin.

### Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Where splashing of concentrate is a concern, use protective glasses with side shield.

#### Skin protection

**Hand protection** Not normally needed.

**Other** Not normally needed.

<b>Respiratory protection</b>	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
<b>Thermal hazards</b>	None known.
<b>General hygiene considerations</b>	When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

<b>Appearance</b>	Clear, transparent liquid
<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	Colorless
<b>Odor</b>	Butyl cellosolve odor
<b>Odor threshold</b>	Not available
<b>pH</b>	7 - 8
<b>Melting point/freezing point</b>	Not applicable / Not available
<b>Initial boiling point and boiling range</b>	208 °F (97.78 °C)
<b>Flash point</b>	> 141.0 °F (> 60.6 °C) Tag Closed Cup
<b>Evaporation rate</b>	< 1 (ethyl ether = 1)
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	17.61 mm Hg
<b>Vapor density</b>	0.712 AIR=1
<b>Relative density</b>	0.99 at 77°F
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Complete
<b>Partition coefficient (n-octanol/water)</b>	Not available
<b>Auto-ignition temperature</b>	Not available
<b>Decomposition temperature</b>	Not available
<b>Viscosity</b>	Not available
<b>Other information</b>	
<b>Density</b>	8.28 Not available
<b>Percent volatile</b>	> 99 %
<b>VOC (Weight %)</b>	4 %

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	May be harmful if inhaled.
-------------------	----------------------------

**Skin contact** 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

**Eye contact** Direct contact with eyes may cause temporary irritation.

**Ingestion** May be harmful if swallowed.

**Symptoms related to the physical, chemical and toxicological characteristics** Direct contact with eyes may cause temporary irritation.

**Information on toxicological effects**

**Acute toxicity** May be harmful if swallowed. May be harmful if inhaled.

<b>Product</b>	<b>Species</b>	<b>Test Results</b>
----------------	----------------	---------------------

TACK-IT

**Acute**

*Dermal*

LD50 Rabbit 23880.5977 mg/kg estimated

*Inhalation*

LC50 Mouse 43750 ppm, 7 Hours estimated

Rat 28125 ppm, 4 Hours estimated

*Oral*

LD50 Guinea pig 75 g/kg estimated

Mouse 75 g/kg estimated

Rabbit 18.2577 g/kg estimated

Rat 35000 mg/kg estimated

<b>Components</b>	<b>Species</b>	<b>Test Results</b>
-------------------	----------------	---------------------

Ethylene glycol monobutyl ether (CAS 111-76-2)

**Acute**

*Dermal*

LD50 Rabbit 400 mg/kg

*Inhalation*

LC50 Mouse 700 ppm, 7 Hours

Rat 450 ppm, 4 Hours

*Oral*

LD50 Guinea pig 1.2 g/kg

Mouse 1.2 g/kg

Rabbit 0.32 g/kg

Rat 560 mg/kg

*Other*

LD50 Mouse 1130 mg/kg

Rabbit 280 mg/kg

Rat 340 mg/kg

Isopropyl Alcohol (CAS 67-63-0)

**Acute**

*Dermal*

LD50 Rabbit 12800 mg/kg

*Oral*

LD50 Mouse 3600 mg/kg

Rabbit 5.03 g/kg

Rat 4.7 g/kg

*Other*

LD50 Mouse 1509 mg/kg

Components	Species	Test Results
	Rat	1099 mg/kg

\* Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

**Serious eye damage/eye irritation** Direct contact with eyes may cause temporary irritation.

**Respiratory or skin sensitization**

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

Ethylene glycol monobutyl ether (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.

**Specific target organ toxicity - single exposure** Not classified.

**Specific target organ toxicity - repeated exposure** Not classified.

**Aspiration hazard** Prolonged inhalation may be harmful.

**Chronic effects** May be harmful if absorbed through skin. Prolonged inhalation may be harmful.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

**12. Ecological information**

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product	Species	Test Results
TACK-IT		
<b>Aquatic</b>		
Fish	LC50	64283.6563 mg/l, 96 hours estimated
<b>Components</b>		
Ethylene glycol monobutyl ether (CAS 111-76-2)		
<b>Aquatic</b>		
Fish	LC50	Inland silverside (Menidia beryllina) 1250 mg/l, 96 hours
Isopropyl Alcohol (CAS 67-63-0)		
<b>Aquatic</b>		
Fish	LC50	Bluegill (Lepomis macrochirus) > 1400 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential**

**Partition coefficient n-octanol / water (log Kow)**

Ethylene glycol monobutyl ether 0.83  
Isopropyl Alcohol 0.05

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

### 14. Transport information

#### DOT

Not regulated as dangerous goods.

### 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
All components are on the U.S. EPA TSCA Inventory List.

#### **TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

#### **CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed.

#### **SARA 304 Emergency release notification**

Not regulated.

#### **US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

#### **Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories** Immediate Hazard - No  
Delayed Hazard - No  
Fire Hazard - Yes  
Pressure Hazard - No  
Reactivity Hazard - No

#### **SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** No

#### **SARA 313 (TRI reporting)**

Not regulated.

#### **Other federal regulations**

**Safe Drinking Water Act (SDWA)** Not regulated.

#### **US state regulations**

##### **US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

##### **US. Massachusetts RTK - Substance List**

Ethylene glycol monobutyl ether (CAS 111-76-2)  
Isopropyl Alcohol (CAS 67-63-0)

##### **US. New Jersey Worker and Community Right-to-Know Act**

Ethylene glycol monobutyl ether (CAS 111-76-2)  
Isopropyl Alcohol (CAS 67-63-0)

##### **US. Pennsylvania Worker and Community Right-to-Know Law**

Ethylene glycol monobutyl ether (CAS 111-76-2)  
Isopropyl Alcohol (CAS 67-63-0)

**US. Rhode Island RTK**

Isopropyl Alcohol (CAS 67-63-0)

**US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

**International Inventories**

<b>Country(s) or region</b>	<b>Inventory name</b>	<b>On inventory (yes/no)*</b>
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision**

<b>Issue date</b>	11-24-2014
<b>Version #</b>	01
<b>HMIS® ratings</b>	Health: 1 Flammability: 2 Physical hazard: 0

**Disclaimer** No representations or warranties, either express or implied, of merchantability, fitness for a particular purpose, or of any nature are made with respect to the product(s) or information contained in this material safety data sheet. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. The buyer or user assumes all risks associated with the use, misuse or disposal of this product. The buyer or user is responsible to comply with all federal, state or local regulations concerning the use, misuse or disposal of these products.