MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

			OR'S INFORMATION				
	Flammability-2; Reactivity-0; Special-0		S Rating: Health-2;			vity-0; Persor	al Protection-B
,			DOT Hazard Classification: ORM-D				
Address:	6600 Governors Lake Pkwy.	Ider	Identity (trade name as used on label):				
Norcross, GA 30071			ALLSTAR SUPER SHINE (U17566)				
Phone: 800-UNISOURCE			MSDS Number: A00 136 Revision- 3				
EMERGENCY RESPONSE NUMBER: 1-888-660-6737			Date Prepared: 04/12/93 Prepared By: ES/KD				
NOTICE: JUDGMENT BASED ON INDIRECT TEST DATA Information Calls: (770)422-2071							
	SECTION 1 - MATERIAL	IDENTIFIC	ATION AND INFOR	MATION	-		
							Carcinogen
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)			0050 44 0	III LIST	(ppm)	TLV (ppm)	Ref. Source **
			8052-41-3	No	100	100	d
ISOBUTANE / PROPANE BLEND			75-28-5	No	800	800	d
		74-98-6	No	1000	1000	d	
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS							
Boiling Point: N/A Specific Gravity (H2O=1): Concentrate Only = 0.980							
			Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A				
			Evaporation Rate (= 1): N/E				
Solubility in Water: Partial Water Reactive: No							
Appearance and Odor: Cream color, with lemon fragrance. SECTION 3 - FIRE AND EXPLOSION HAZARD DATA							
(aerosols) 12-16 In	USA FLAME PROJECTION TEST Inch Flame Extension	•	ition Temperature N/E	% LEL	nability Limits .: N/E	% ÜEL:	N/E
FLASH POINT AND METHOD USED (non-aerosols): N/A EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water fog. SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.							
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.							
SECTION 4 - REACTIVITY HAZARD DATA							
STABILITY [X]S	TABLE [] UNSTABLE		ARDOUS POLYME	RIZATIC	dn [] Wi	L [X]W	ILL NOT
OCCUR Incompatibility (Mat. to avoid): Strong oxidizers. Conditions to Avoid: Open flame, welding arcs, heat, sparks.							
		001		open nan	ne, weiding a	103, 110at, 3p	Janko.
Hazardous Decomposition Products: CO, CO2.							
SECTION 5 - HEALTH HAZARD DATA							
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION [X]SKIN ABSORPTION []EYE []NOT HAZARDOUS							
ACUTE EFFECTS:							
Inhalation: Excessive inhalation of vapors can be harmful amd may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.							
Eye Contact: Slight irritation. Skin Contact: Slight irritation.							
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.							
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) Petroleum distillate has caused kidney injury in laboratory animals. Stomach and intestine irritant.							
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.							
EMERGENCY FIRST AID PROCEDURES							
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.							
Skin Contact: Wash with soap and water. If irritated, seek medical attention.							
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.							
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.							
SECTION 6 - CONTROL AND PROTECTIVE MEASURES							
Respiratory Protection vapor.	n (specify type): If vapor concentration	exceeds TL	V, use respirator ap	proved by	y U.S. Burea	u of Mines fo	or organic
	itex, if skin easily irritated.	Eye	Protection: Safety	glasses	recommend	ed.	
Ventilation Requireme	ents: Adequate ventilation to keep vapo	r concentrat	ion below TLV.				
	ning & Equipment: None						
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.							
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE							
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations. DO NOT FLUSH TO SEWER.							
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.							
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.							
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors.							
Remove ignition source							
We believe the statemen	ts, technical information and recommendation	s contained he kind	erein are reliable, but tl	ney are giv	en without wa	rranty or guar	antee of any

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only THIS MSDS IS CURRENT AS OF March 18, 2001. The DATE PREPARED section is the original date assembled and remains current until a change is necessary. This is tracked internally at the manufacturer by these date codes and therefore must remain as the originating date.