MSDS Number: C5949 \* \* \* \* \* Effective Date: 03/03/11 \* \* \* \* \* Supersedes: 11/21/08



From: Avantor Performance Materials, Inc. Saucon Valley Plaza 3477 Corporate Parkway Suite #200 Center Valley, PA 18034





24 Hour Emergency Telephone: 908-859-2151 CHEMTREC: 1-800-424-9300

National Response in Canada CANUTEC: 613-996-6666

Outside U.S. and Canada Chemtrec: 703-527-3887

NOTE: CHEMTREC, CANUTEC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

All non-emergency questions should be directed to Customer Service, 1-855-AVANTOR (855-282-6867) for assistance.

# **CUPROUS CHLORIDE**

## 1. Product Identification

**Synonyms:** Copper (1) chloride; copper monochloride

CAS No.: 7758-89-6 Molecular Weight: 99.00 Chemical Formula: CuCl

**Product Codes:** J.T. Baker: 1862 Macron: 4860

# 2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
Copper Chloride	7758-89-6	100%	Yes

# 3. Hazards Identification

**Emergency Overview** 

WARNING! HARMFUL IF SWALLOWED OR INHALED. AFFECTS THE LIVER AND KIDNEYS. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT.

**SAF-T-DATA**(tm) Ratings (Provided here for your convenience)

Health Rating: 3 - Severe (Poison) Flammability Rating: 0 - None Reactivity Rating: 2 - Moderate

Contact Rating: 3 - Severe (Corrosive)

Lab Protective Equip: GOGGLES & SHIELD; LAB COAT & APRON; VENT HOOD; PROPER GLOVES

Storage Color Code: White (Corrosive)

-----

### **Inhalation:**

Causes irritation to respiratory tract, symptoms may include coughing, sore throat, and shortness of breath. May result in ulceration and perforation of respiratory tract. When heated, this compound may give off copper fume, which can cause symptoms similar to the common cold, including chills and stuffiness of the head.

## **Ingestion:**

May cause burning pain in the mouth, esophagus, and stomach. Hemorrhagic gastritis, nausea, vomiting, abdominal pain, metallic taste, and diarrhea may occur. If vomiting does not occur immediately systemic copper poisoning may occur. Symptoms may include capillary damage, headache, cold sweat, weak pulse, kidney and liver damage, central nervous excitation followed by depression, jaundice, convulsions, blood effects, paralysis and coma. Death may occur from shock or renal failure.

### **Skin Contact:**

Causes irritation, redness, and pain. Some individuals may develop copper allergies.

### **Eye Contact:**

Causes irritation, redness, pain, discoloration and damage. May cause conjunctivitis, ulceration or clouding of the cornea.

## **Chronic Exposure:**

Prolonged or repeated skin exposure may cause dermatitis. Prolonged or repeated exposure to dusts of copper salts may cause discoloration of the skin or hair, blood and liver damage, ulceration and perforation of the nasal septum, runny nose, metallic taste, and atrophic changes and irritation of the mucous membranes.

## **Aggravation of Pre-existing Conditions:**

Persons with pre-existing skin disorders, impaired liver, kidney, or pulmonary function, glucose 6-phosphate-dehydrogenase deficiency, or pre-existing Wilson's disease may be more susceptible to the effects of this material.

# 4. First Aid Measures

### **Inhalation:**

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

## **Ingestion:**

Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Call a physician immediately.

### **Skin Contact:**

In case of contact, wipe off excess material from skin then immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician.

### **Eye Contact:**

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

# 5. Fire Fighting Measures

#### Fire:

Not considered to be a fire hazard.

### **Explosion:**

Not considered to be an explosion hazard. Reactions with incompatibles may pose an explosion hazard.

## Fire Extinguishing Media:

Use any means suitable for extinguishing surrounding fire. Water spray may be used to keep fire exposed containers cool.

### **Special Information:**

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

## 6. Accidental Release Measures

Ventilate area of leak or spill. Keep unnecessary and unprotected people away from area of spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Pick up and place in a suitable container for reclamation or disposal, using a method that does not generate dust. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

# 7. Handling and Storage

Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against physical damage. Isolate from incompatible substances. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product.

# 8. Exposure Controls/Personal Protection

### **Airborne Exposure Limits:**

-OSHA Permissible Exposure Limit (PEL):

1 mg/m3 (TWA) for copper dusts & mists as Cu

-ACGIH Threshold Limit Value (TLV):

1 mg/m3 (TWA) for copper dusts & mists as Cu

### **Ventilation System:**

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

### **Personal Respirators (NIOSH Approved):**

If the exposure limit is exceeded and engineering controls are not feasible, a half facepiece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest.. A full-face piece particulate respirator (NIOSH type N100 filters) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

## **Skin Protection:**

Wear protective gloves and clean body-covering clothing.

#### **Eve Protection:**

Use chemical safety goggles and/or full face shield where dusting or splashing of solutions is possible. Maintain eye wash fountain and quick-drench facilities in work area.

# 9. Physical and Chemical Properties

Appearance:

White crystals.

Odor:

Odorless.

**Solubility:** 

0.62g/100 ml water.

**Specific Gravity:** 

4.14

# pH:

No information found.

% Volatiles by volume @ 21C (70F):

0

### **Boiling Point:**

1490C (2714F)

## **Melting Point:**

430C (806F)

## Vapor Density (Air=1):

No information found.

## **Vapor Pressure (mm Hg):**

0.975 @ 546C (1015F)

## **Evaporation Rate (BuAc=1):**

No information found.

# 10. Stability and Reactivity

## **Stability:**

Stable under ordinary conditions of use and storage. Turns green on exposure to moist air. Turns brown on exposure to light.

## **Hazardous Decomposition Products:**

Oxides of the contained metal and halogen, possibly also free, or ionic halogen.

## **Hazardous Polymerization:**

Will not occur.

# **Incompatibilities:**

Potassium, acetylene, hydrazine, and nitromethane. Reacts violently with lithium nitride and heat.

## **Conditions to Avoid:**

Moisture, light, incompatibles.

# 11. Toxicological Information

Oral rat LD50: 140 mg/kg; Inhalation mouse LC50: 1008 mg/m3; investigated as a mutagen.

\Cancer Lists\				
	NTP Carcinogen			
Ingredient	Known	Anticipated	IARC Category	
Copper Chloride (7758-89-6)	No	No	None	

# 12. Ecological Information

### **Environmental Fate:**

When released into the soil, this material is not expected to biodegrade. When released into the soil, this material is not expected to evaporate significantly. When released into water, this material is not expected to biodegrade. When released into water, this material is not expected to evaporate significantly.

## **Environmental Toxicity:**

No information found.

# 13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

# 14. Transport Information

**Domestic (Land, D.O.T.)** 

**Proper Shipping Name:** COPPER CHLORIDE

Hazard Class: 8 UN/NA: UN2802 Packing Group: III

Information reported for product/size: 500G

**International (Water, I.M.O.)** 

-----

**Proper Shipping Name:** COPPER CHLORIDE

Hazard Class: 8 UN/NA: UN2802 Packing Group: III

Information reported for product/size: 500G

**International (Air, I.C.A.O.)** 

-----

**Proper Shipping Name:** COPPER CHLORIDE

Hazard Class: 8 UN/NA: UN2802 Packing Group: III

Information reported for product/size: 500G

# 15. Regulatory Information

Ingredient	-		EC	Japan	Australia	
Copper Chloride (7758-89-6)				Yes		
\Chemical Inventory Status - Part 2	2\			 anada		
Ingredient		Korea		NDSL		
Copper Chloride (7758-89-6)		Yes		No		
\Federal, State & International Regulations - Part 1\SARA 313						
Ingredient					mical Catg.	
Copper Chloride (7758-89-6)	No	No			per compo	
\Federal, State & International Reg	gulatio			2\ T:		

Ingredient	CERCLA	261.33	8(d)
Copper Chloride (7758-89-6)	No	No	No

Chemical Weapons Convention: No TSCA 12(b): No CDTA: No SARA 311/312: Acute: Yes Chronic: Yes Fire: No Pressure: No

Reactivity: No (Pure / Solid)

Australian Hazchem Code: 2Z Poison Schedule: None allocated.

WHMIS:

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

# 16. Other Information

NFPA Ratings: Health: 2 Flammability: 0 Reactivity: 0

**Label Hazard Warning:** 

WARNING! HARMFUL IF SWALLOWED OR INHALED. AFFECTS THE LIVER AND KIDNEYS.

CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT.

**Label Precautions:** 

Avoid breathing dust.

Keep container closed.

Use with adequate ventilation.

Wash thoroughly after handling.

Avoid contact with eyes, skin and clothing.

### **Label First Aid:**

If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Call a physician immediately. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician. In case of contact, wipe off excess material from skin then immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician.

### **Product Use:**

Laboratory Reagent.

## **Revision Information:**

No Changes.

#### Disclaimer:

THE INFORMATION PRESENTED IN THIS MATERIAL SAFETY DATA SHEET (MSDS/SDS) WAS PREPARED BY TECHNICAL PERSONNEL BASED ON DATA THAT THEY BELIEVE IN THEIR GOOD FAITH JUDGMENT IS ACCURATE. HOWEVER, THE INFORMATION PROVIDED HEREIN IS PROVIDED "AS IS," AND AVANTOR PERFORMANCE MATERIALS MAKES AND GIVES NO REPRESENTATIONS OR WARRANTIES WHATSOEVER, AND EXPRESSLY DISCLAIMS ALL WARRANTIES REGARDING SUCH INFORMATION AND THE PRODUCT TO WHICH IT RELATES, WHETHER EXPRESS, IMPLIED, OR STATUTORY, INCLUDING WITHOUT LIMITATION, WARRANTIES OF ACCURACY, COMPLETENESS, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY, STABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, AND ANY WARRANTIES ARISING FROM COURSE OF DEALING, COURSE OF PERFORMANCE, OR USAGE OF TRADE.

continued

THIS MSDS/SDS IS INTENDED ONLY AS A GUIDE TO THE APPROPRIATE PRECAUTIONARY HANDLING OF THE MATERIAL BY A PROPERLY TRAINED PERSON USING THIS PRODUCT, AND IS NOT INTENDED TO BE COMPREHENSIVE AS TO THE MANNER AND CONDITIONS OF USE, HANDLING, STORAGE, OR DISPOSAL OF THE PRODUCT. INDIVIDUALS RECEIVING THIS MSDS/SDS MUST ALWAYS EXERCISE THEIR OWN INDEPENDENT JUDGMENT IN DETERMINING THE APPROPRIATENESS OF SUCH ISSUES. ACCORDINGLY, AVANTOR PERFORMANCE MATERIALS ASSUMES NO LIABILITY WHATSOEVER FOR THE USE OF OR RELIANCE UPON THIS INFORMATION. NO SUGGESTIONS FOR USE ARE INTENDED AS, AND NOTHING HEREIN SHALL BE CONSTRUED AS, A RECOMMENDATION TO INFRINGE ANY EXISTING PATENTS OR TO VIOLATE ANY FEDERAL, STATE, LOCAL, OR FOREIGN LAWS. AVANTOR PERFORMANCE MATERIALS REMINDS YOU THAT IT IS YOUR LEGAL DUTY TO MAKE ALL INFORMATION IN THIS MSDS/SDS AVAILABLE TO YOUR EMPLOYEES.

\*

**Prepared by:** Environmental Health & Safety