

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name

Product Code Revision Date: Print Date: Product Class Color Recommended use Restrictions on use V-PRO 5000 EGGSHELL .5300 11/06/2015 2016-01-13 WATER THINNED PAINT White Paint No information available

Manufacturer Vista Paint Corporation 2020 E. Orangethorpe Ave. Fullerton, CA 92831 714.680.3800

Emergency Telephone Number(s): 800.535.5053 (Infotrac)

2. HAZARD(S) IDENTIFICATION

GHS Pictograms:	
Signal Word:	Warning
GHS Classifications:	H319 - Eye irritant
	H315 – Škin Irritant
Hazard Statements:	Causes eye and skin irritation
Precautionary Statements:	P103 – Read label before use.
	P261 – Avoid breathing dust/fume/gas/mist/vapors/spray.
	P264 – Wash hands thoroughly after handling.
	P273 – Avoid release to the environment.
	P281 – Wear protective equipment as required – respirator/safety glasses/gloves.
	P285 – In case of inadequate ventilation wear respiratory protection.
	P301 + P310 – IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
	P302 + P350 – IF ON SKIN: Gently wash with plenty of water and soap.
	P305 + P351 + P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lens, if present and easy to do. Continue rinsing.
	P501 – Dispose of contents/container in accordance with local/state/federal regulations.
HNOC:	Not Applicable
Other information:	No information available

3. COMPOSITION INFORMATION ON COMPONENTS

Hazardous Component	CAS Number	Weight %
Titanium Dioxide	13463-67-7	13.38
Aluminum Silicate - KAOLIN	1332-58-7	10.88
Calcium Carbonate	1317-65-3	6.01

	4. FIRST AID MEASURES		
General Advice:	No hazards which require special first aid measures.		
Eye Contact:	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.		
Skin Contact:	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.		
Inhalation:	Move to fresh air. If symptoms persist, call a physician.		
Ingestion:	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.		
Most Important Symptoms/Effects:	None known.		
Notes To Physician:	Treat symptomatically.		

5. FIRE-FIGHTING MEASURES

NFPA:	1 - 0 - 0
Suitable Extinguishing Media:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective Equipment And Precautions For Firefighters:	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Specific Hazards Arising From The Chemical:	Closed containers may rupture if exposed to fire or extreme heat

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.
Other Information:	Prevent further leakage or spillage if safe to do so.
Environmental Precautions:	See Section 12 for additional Ecological Information.
Methods For Clean-Up:	Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling:	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.		
Storage:	Keep container tightly closed. Keep out of the reach of children. Keep from freezing.		
Incompatible Materials:	No information available		

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

REPORTABLE COMPONENTS	CAS NUMB	WT ER %	AGCIH LV/TWA PPM	OSI TW PPM	HA Exposure Li /A STEL MG/M3 PPM			Vapor Pressure mm Hg @temp
Titanium Dioxide	13463-67-7	13.38	10	-	10	-	-	-
Aluminum Silicate - KAOLIN	1332-58-7	10.88	-	-	15	-	-	-
Calcium Carbonate	1317-65-3	6.01	-	-	15	-	-	-

Eye/Face Protection:	Safety glasses with side-shields.
Skin Protection	Protective gloves and impervious clothing.
Respiratory Protection	In case of insufficient ventilation wear suitable respiratory equipment.
Engineering Measures:	Ensure adequate ventilation, especially in confined areas.
Hygiene Measures:	Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Product Code: .5300

Product Name: V-PRO 5000 EGGSHELL

Liquid Vista Paint Corporation

Odor **Odor Threshold** Density (lbs./gal) 10.63 Specific Gravity 1.28 рĤ Viscosity (cps) Solubility Water Solubility **Evaporation Rate** Vapor Pressure Vapor Density Wt. % Solids 52.46 Vol. % Solids 40.88 Wt. % Volatiles 47.54 Vol. % Volatiles 40.88 **Coating VOC** 1.07 g/l **Material VOC** 0.44 g/l **Boiling Point (°F)** 212 °Ĕ 32 °F Freezing Point (°F) Flash Point (°F) **Flash Point Method** Flammability (solid, gas) **Upper Explosion Limit** Lower Explosion Limit Autoignition Temperature (°F) Decomposition Temperature (°F) Partition Coefficient (n-octanol/water)

Little or no odor No information available Not applicable Not applicable Not applicable Not applicable Not applicable No information available No information available No information available

10. STABILITY AND REACTIVITY

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Conditions To Avoid	Prevent from freezing
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility Of Hazardous Reactions	None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Principal Routes of Exposure:	Eye contact, skin contact	t and inhalation.
Acute Toxicity:	No information available	
Symptoms	No information available	
Eye contact	May cause slight irritation	n.
Skin contact	Substance may cause sl	ight skin irritation. Prolonged or
Product Name: V-PRO 5000 EGGSHELL	Vista Paint Corporation	Page 4 of 7
Product Code: .5300		

	repeated contact may dry skin and cause irritation.
Inhalation	May cause irritation of respiratory tract.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Sensitization:	No information available
Neurological Effects	No information available.
Mutagenic Effects	No information available.
Reproductive Effects	No information available.
Developmental Effects	No information available.
Target Organ Effects	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Other adverse effects	No information available.
Aspiration Hazard	No information available

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical Name	IARC	NTP	OSHA Carcinogen
	2B - Possible Human		Listed
Titanium dioxide	Carcinogen		

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION			
Ecotoxicity Effects	The environmental impact of this product has not been fully investigated.		
Acute Toxicity to Fish (Titanium Dioxide)	LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)		
Acute Toxicity to Aquatic Invertebrates	No information available		

Acute Toxicity to Aquatic Plants	No information available
Persistence / Degradability	No information available
Bioaccumulation / Accumulation	No information available
Mobility in Environmental Media	No information available
Ozone	No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal MethodDispose of in accordance with federal, state, provincial, and local regulations.
Local requirements may vary, consult your sanitation department or
state-designated environmental protection agency for more disposal options.

	14. TRANSPORT INFORMATION	
DOT	Not regulated	
ICAO / IATA	Not regulated	
IMDG / IMO	Not regulated	

15. REGULATORY INFORMATION

International Inventories

TSCA: United States	Yes - All components are listed or exempt.
DSL: Canada	Yes - All components are listed or exempt.

Federal Regulations

SARA 311/312 hazardous categorization

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Aluminum Silicate - 1332-58-7 KAOLIN

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs: None

State Regulations

California Proposition 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm at levels less than required for reporting (<0.1%) unless listed in section III.

16. OTHER INFORMATION						
<u>HMIS</u>	Health: 1*	Flammability: 0	Reactivity: 0	PPE: X		
Prepared E	Ared ByVista Paint Corporation2020 East Orangethorpe AvenueFullerton, CA92831714.680.3800					
SDS Form	Date:	2015.12.31	2015.12.31			
Revision S	Summary	Not available				

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET