

M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT CODE: 1240001

Page 1 of 3

PRODUCT NAME: MIRRO GLIDE S/G WHITE BASE HMIS CODES: H C F R P
PRODUCT CODE: 1240001 1 0 0 0 G

=====**SECTION I - MANUFACTURER IDENTIFICATION**=====

MANUFACTURER'S NAME: Frazee Industries
ADDRESS : 6625 Miramar Rd.
 San Diego, CA, 92121
INFORMATION PHONE : 858-626-3600 DATE PRINTED : 4/19/2010
EMERGENCY PHONE: (619) 543-6000 (SAN DIEGO REGIONAL POISON CONTROL CENTER)

=====**SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION**=====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg	@ TEMP	WEIGHT PERCENT
PROPYLENE GLYCOL OSHA: N/E, ACGIH TLV: N/E, OTHER: N/E	57-55-6	0.08	68 F	1

* Indicates toxic chemical (s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

PROPOSITION 65: (+) See section VI

=====**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**=====

BOILING POINT: 212 F.DEG. (WATER)	SPECIFIC GRAVITY (H2O=1): 1.21
VAPOR DENSITY: HEAVIER THAN AIR	EVAPORATION RATE: SLOWER THAN ETHER
COATING VOC g/Lt 49.9	MATERIAL VOC g/Lt 18.9
#VOC/#SOLIDS 0.0324	

SOLUBILITY IN WATER: DILUTABLE
APPEARANCE AND ODOR: VISCIOUS LIQUID. MILD ODOR.

=====**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**=====

FLASH POINT: N/A METHOD USED: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A
EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG
SPECIAL FIREFIGHTING PROCEDURES: WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD UP WHEN EXPOSED TO EXTREME HEAT. WEAR ADEQUATE FIRE FIGHTING EQUIPMENT INCLUDING A SELF CONTAINED BREATHING APPARATUS
UNUSUAL FIRE AND EXPLOSION HAZARDS: POLYMER FILM CAN BURN. MATERIAL CAN SPLATTER ABOVE 212 F. DEG.

=====**SECTION V - REACTIVITY DATA**=====

STABILITY: STABLE
CONDITIONS TO AVOID
EXCESS HEAT MAY CAUSE CONTAINERS TO RUPTURE. AVOID TEMPERATURES BELOW 40 F. DEG. AVOID FREEZING CONDITIONS.
INCOMPATIBILITY (MATERIALS TO AVOID)
AVOID MATERIALS THAT ARE WATER REACTIVE. ALSO AVOID STRONG ALKALINE AND ACIDIC SUBSTANCES.
HAZARDOUS DECOMPOSITION OR BYPRODUCTS
CO, CO2, VARIOUS HYDROCARBONS, ETC., BY COMBUSTION.

M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT CODE: 1240001

Page 2 of 3

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR

=====**SECTION VI - HEALTH HAZARD DATA**=====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

VAPOR OR MIST CAN CAUSE HEADACHE, NAUSEA AND IRRITATION OF THE NOSE, THROAT AND LUNGS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

USE GOOD PERSONAL HYGIENE PRACTICES WHILE WORKING WITH THIS MATERIAL. DRY CONTAMINATED CLOTHING BEFORE REUSE. FOR EYE CONTACT, FLUSH WITH FRESH WATER FOR AT LEAST 15 MINUTES. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

NONE EXPECTED.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

MAY BE HARMFUL OR FATAL IF SWALLOWED. INGESTION MAY CAUSE NAUSEA, VOMITING, DIARRHEA AND GASTROINTESTINAL IRRITATION. CONSULT A PHYSICIAN.

HEALTH HAZARDS (ACUTE AND CHRONIC)

NONE EXPECTED.

CARCINOGENICITY:

NTP CARCINOGEN: No IARC MONOGRAPHS: N/A OSHA REGULATED: No

PROPOSITION 65: N/A

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

OVEREXPOSURE TO VAPORS CAN CAUSE HEADACHES, DIZZINESS AND NAUSEA.

EMERGENCY AND FIRST AID PROCEDURES

DERMAL: CLEAN WITH SOAP AND WATER. □

INGESTION. CONSULT A PHYSICIAN. □

INHALATION: REMOVE TO FRESH AIR. □

EYE CONTACT: FLUSH WITH WATER. CONSULT A PHYSICIAN.

=====**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**=====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

WIPE UP IMMEDIATELY AND SAFELY DISCARD ABSORBANTS. IN THE EVENT OF LARGE SPILLS, DIKE THE AREA AND PUMP THE MATERIAL TO AN EPA PERMITTED WASTE TANK.

WASTE DISPOSAL METHOD

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS CURRENTLY IN FORCE FOR THIS PRODUCT HAZARD CLASS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

USE WITH ADEQUATE VENTILATION. AVOID PROLONGED BREATHING VAPOR. AVOID PROLONGED OR REPEATED SKIN CONTACT. KEEP AWAY FROM EXCESSIVE HEAT.

OTHER PRECAUTIONS

AVOID ALL SOURCES OF HEAT, OPEN FLAMES, SPARKS AND STATIC ELECTRICITY.

=====**SECTION VIII - CONTROL MEASURES**=====

RESPIRATORY PROTECTION: NONE REQUIRED IF AIRBORNE CONCENTRATIONS ARE MAINTAINED BELOW THE OCCUPATIONAL EXPOSURE LIMITS LISTED IN SECTION II. FOR AIRBORNE CONCENTRATIONS HIGHER THAN SUCH LIMITS WEAR A MSHA/NIOSH APPROVED MASK FOR ORGANIC VAPOR, DUST, MIST & FUMES. WHEN USING IN POORLY VENTILATED AND CONFINED SPACES USE A FRESH-AIR SUPPLYING OR SELF-CONTAINED BREATHING APPARATUS.

VENTILATION: MAINTAIN GOOD VENTILATION TO KEEP PRODUCT VAPOR CONCENTRATIONS BELOW SPECIFIED THRESHOLD LIMIT VALUES.

PROTECTIVE GLOVES: NEOPRENE GLOVES SHOULD BE WORN TO REDUCE THE EFFECTS OF SKIN OVER-EXPOSURE.

EYE PROTECTION: GOGGLES OR FACE SHIELD ARE RECOMMENDED.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: TO PREVENT REPEATED OR PROLONGED SKIN CONTACT, WEAR PROTECTIVE CLOTHING AND BOOTS.

M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT CODE: 1240001

Page 3 of 3

WORK/HYGIENIC PRACTICES: EYE WASHES & SAFETY SHOWERS IN THE WORKPLACE ARE RECOMMENDED, AS WELL AS BARRIER CREAMS, DAILY SHOWERS & CHANGE OF CLOTHES.

===== SECTION IX - DISCLAIMER =====

NOTICE: TO THE BEST OF OUR KNOWLEDGE THIS INFORMATION IS ACCURATE. HOWEVER, WE DO NOT GUARANTEE ITS ACCURACY AND CANNOT BE LIABLE FOR ANY DAMAGES ACTUAL OR CONSEQUENTIAL WHICH MIGHT RESULT FROM RELIANCE THEREON.