



Material Safety Data Sheet

Material Name: BEST TEST Paper Cement

MSDS ID: UR-002

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Name: BEST TEST Paper Cement

Manufacturer Information

Union Rubber, Inc.
232 Allen Street
P.O. Box 1040
Trenton, NJ 08606

Phone: 609-396-9328

Fax: 609-396-3587

Emergency: Chemtrec: 800-424-9300

Section 2 - HAZARDS IDENTIFICATION

NFPA Ratings: Health: 2 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

EMERGENCY OVERVIEW

Color: pale, straw colored

Physical Form: liquid

Odor: pleasant odor

Health Hazards: respiratory tract irritation, skin irritation, eye irritation, central nervous system depression

Physical Hazards: Flammable liquid and vapor. Vapor may cause flash fire. Electrostatic charges may be generated by flow, agitation, etc.

POTENTIAL HEALTH EFFECTS

Inhalation

Short Term: irritation, headache, drowsiness, dizziness, emotional disturbances, loss of coordination, fatigue, nausea, suffocation, unconsciousness

Long Term: no information is available

Skin

Short Term: irritation

Long Term: irritation

Eye

Short Term: irritation

Long Term: irritation

Ingestion

Short Term: gastrointestinal irritation, nausea, vomiting, diarrhea, stomach pain, headache, drowsiness, dizziness, emotional disturbances, loss of coordination, unconsciousness

Long Term: no information is available

Regulatory Status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). This material is a controlled product under Canadian WHMIS regulations.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component	Percent
142-82-5	Heptane	87
9003-31-0	1,3-Butadiene, 2-methyl-, homopolymer	12.9
Not Available	Non-hazardous processing aids	0.1

Component Related Regulatory Information

This product may be regulated, have exposure limits or other information identified as the following: Heptane isomers.

Material Safety Data Sheet

Material Name: BEST TEST Paper Cement

MSDS ID: UR-002

Section 4 - FIRST AID MEASURES

Inhalation

If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

Skin

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

Eyes

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

Ingestion

If a large amount is swallowed, get medical attention.

Note to Physicians

For inhalation, consider oxygen.

Section 5 - FIRE FIGHTING MEASURES

See Section 9 for Flammability Properties

Flammable Properties

Severe fire hazard. The vapor is heavier than air. Vapors or gases may ignite at distant ignition sources and flash back. Vapor/air mixtures are explosive. Electrostatic discharges may be generated by flow or agitation resulting in ignition or explosion.

Extinguishing Media

regular dry chemical, carbon dioxide, water spray, regular foam

Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Fire Fighting Measures

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For tank, rail car or tank truck: Evacuation radius: 800 meters (1/2 mile). Water may be ineffective.

Hazardous Combustion Products

Combustion: aldehydes, oxides of carbon

Sensitivity to Mechanical Impact

Not sensitive

Sensitivity to Static Discharge

Yes

Section 6 - ACCIDENTAL RELEASE MEASURES

Occupational spill/release

Avoid heat, flames, sparks and other sources of ignition. Stop leak if possible without personal risk. Reduce vapors with water spray. **Small spills:** Absorb with sand or other non-combustible material. Collect spilled material in appropriate container for disposal. **Large spills:** Dike for later disposal. Remove sources of ignition. Keep unnecessary people away, isolate hazard area and deny entry.

Section 7 - HANDLING AND STORAGE

Handling Procedures

Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Wash thoroughly after handling. Keep away from heat, sparks and flame.

Material Safety Data Sheet

Material Name: BEST TEST Paper Cement

MSDS ID: UR-002

Storage Procedures

Store and handle in accordance with all current regulations and standards. Subject to storage regulations: U.S. OSHA 29 CFR 1910.106. Grounding and bonding required. Avoid heat, flames, sparks and other sources of ignition. Keep separated from incompatible substances. Store in a well-ventilated area. Keep container tightly closed.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Heptane (142-82-5)

ACGIH: 400 ppm TWA
500 ppm STEL
NIOSH: 85 ppm TWA; 350 mg/m³ TWA
440 ppm Ceiling (15 min); 1800 mg/m³ Ceiling (15 min)
750 ppm IDLH
Europe: 500 ppm TWA; 2085 mg/m³ TWA
OSHA (US): 500 ppm TWA; 2000 mg/m³ TWA
Mexico: 400 ppm TWA; 1600 mg/m³ TWA
500 ppm STEL; 2000 mg/m³ STEL
Skin - potential for cutaneous absorption

Ventilation

Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

Eyes/Face

Wear splash resistant safety goggles with a faceshield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Protective Clothing

Wear appropriate chemical resistant clothing.

Glove Recommendations

Wear appropriate chemical resistant gloves.

Respiratory Protection

Under conditions of frequent use or heavy exposure, respiratory protection may be needed.

Respiratory protection is ranked in order from minimum to maximum.

Consider warning properties before use.

Any chemical cartridge respirator with organic vapor cartridge(s).

Any chemical cartridge respirator with a full facepiece and organic vapor cartridge(s).

Any air-purifying respirator with a full facepiece and an organic vapor canister.

For Unknown Concentrations or Immediately Dangerous to Life or Health -

Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive-pressure mode.

Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

Material Safety Data Sheet

Material Name: BEST TEST Paper Cement

MSDS ID: UR-002

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid	Appearance:	pale, straw colored, liquid
Color:	pale, straw colored	Physical Form:	liquid
Odor:	pleasant odor	Odor Threshold:	Not available
pH:	essentially neutral	Melting/Freezing Point:	Not available
Boiling Point:	92-100 °C	Flash Point:	-6.7 °C
Evaporation Rate:	4.5 (butyl acetate=1)	LEL:	1.1 % (estimated)
UEL:	Not available	Vapor Pressure:	~40 mmHg @20 °C
Vapor Density (air = 1):	~3.5	Density:	Not available
Specific Gravity (water = 1):	0.70	Water Solubility:	Not available
Coeff. Water/Oil Dist:	Not available	Auto Ignition:	Not available
Viscosity:	6.5 (Gardner scale)	VOC:	5.04 lbs/gal
Volatility:	91 % @25 °C		

Section 10 - STABILITY AND REACTIVITY

Chemical Stability

Stable at normal temperatures and pressure.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Containers may rupture or explode if exposed to heat. Keep out of water supplies and sewers.

Materials to Avoid

calcium hypochlorite, combustible materials, concentrated oxygen, liquid chlorine, oxidizing materials, sodium hypochlorite

Hazardous Decomposition

Combustion: aldehydes, oxides of carbon

Possibility of Hazardous Reactions

Will not polymerize.

Section 11 - TOXICOLOGICAL INFORMATION

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Heptane (142-82-5)

Inhalation LC50 Rat 103 g/m³ 4 h; Oral LD50 Mouse 5000 mg/kg; Dermal LD50 Rabbit 3000 mg/kg

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA.

Irritation

Causes skin, eye and respiratory irritation.

Target Organs

central nervous system

Medical Conditions Aggravated by Exposure

respiratory disorders, skin disorders and allergies

Tumorigenic

No data available for the mixture.

Mutagenic

No data available for the mixture.

Reproductive Effects

No data available for the mixture.

Material Safety Data Sheet

Material Name: BEST TEST Paper Cement

MSDS ID: UR-002

Section 12 - ECOLOGICAL INFORMATION

Component Analysis - Aquatic Toxicity

Heptane (142-82-5)

Fish: 96 Hr LC50 Cichlid fish: 375.0 mg/L
Invertebrate: 24 Hr EC50 Daphnia magna: >10 mg/L

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262.
Hazardous Waste Number(s): D001.

Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components.

Section 14 - TRANSPORT INFORMATION

US DOT Information (49 CFR)

Shipping Name: Adhesives
UN/NA #: UN1133 Hazard Class: 3 Packing Group: II
Required Label(s): 3

TDG Information

Shipping Name: Adhesives
UN #: UN1133 Hazard Class: 3 Packing Group: II
Required Label(s): 3

IATA Information

Shipping Name: Adhesives
UN #: UN1133 Hazard Class: 3 Packing Group: II
Required Label(s): 3

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Heptane (142-82-5)

TSCA 12b: Section 4, 1 % de minimus concentration

SARA 311/312

Acute Health: Yes Chronic Health: No Fire: Yes Pressure: No Reactive: No

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Heptane	142-82-5	Yes	Yes	Yes	Yes	Yes	Yes

Not regulated under California Proposition 65

Canada

This product has been classified in accordance with the criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

Material Safety Data Sheet

Material Name: BEST TEST Paper Cement

MSDS ID: UR-002

Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which fall under WHMIS criteria specified in the Controlled Products Regulations and present above the threshold limits listed on the IDL.

Heptane (142-82-5)

1 %

WHMIS Classification

B2, D2B.

U.S. Inventory (TSCA)

All the components of this substance are listed on or are exempt from the inventory.

Component Analysis - Inventory

Component	CAS	US	CA
Heptane	142-82-5	Yes	DSL
1,3-Butadiene, 2-methyl-, homopolymer	9003-31-0	Yes	DSL

Section 16 - OTHER INFORMATION

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSL - Domestic Substances List; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; RID - European Rail Transport; RTECS - Registry of Toxic Effects of Chemical Substances®; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States

Disclaimer

UNION RUBBER INCORPORATED believes that the information contained herein is accurate and reliable as of the date of this material safety data sheet, but no representation guarantee or warranty, express or implied, is made as to the accuracy, reliability, or completeness of the information. Persons receiving this information are encouraged to make their own determination as to the information's suitability and completeness for their particular application. NO INFORMATION CONTAINED HEREIN CONSTITUTES A PRODUCT WARRANTY OF ANY KIND, WHETHER EXPRESS OR IMPLIED; AND ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND OF FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED BY UNION RUBBER INCORPORATED.

End of Sheet UR-002