Material Safety Data Sheet Cutex Regular Nail Polish Remover

901025

The Cutex Company 3510 N. Lake Creek Drive Jackson, WY 83001 307-733-1680

SECTION I: CHEMICAL IDENTIFICATION

Product Name:

Cutex Regular Nail Polish Remover with Acetone

Product Code:

PN 679 (VIJ)

Date Prepared:

January 14, 2000, updated September 2003

Product Use:

Nail Polish Remover

Manufactured for: The Cutex Company

FOR MORE INFORMATION CALL:

IN CASE OF AN EMERGENCY:

800-443-4908

307-733-1680

SECTION II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components

OSHA PEL

ACGIH TLV

% Content

NFPA Hazard Identification:

National Fire Protection Association(NFPA; Legend:

HEALTH 1

3=Serious

FIRE = 3 REACTIVITY = 0

2=Moderate 1=Slight 0=Minimal

4=Extreme

UN Number UN 1090

Emergency Overview: Regular Nail Polish Remover (NPR) is a yellow liquid possessing a sweet, flowery odor. It is a volatile substance in that it is extremely flammable and its vapors form explosive mixtures with air. Since NPR vapors travel with air currents, they can be ignited by spark or flame remote from the site the NPR is being handled. Dangerous fire hazard when exposed to heat, sparks, flame, or oxidants. Eye and mucous membrane irritant. Harmful if swallowed or inhaled.

Additional information Section VI.

SECTION III: PHYSICAL AND CHEMICAL CHARACTERISTICS

Appearance:

Clear liquid with a yellow color.

Physical State:

Liquid.

Odor:

Residual flowery fragrance.

Boiling Point:

approximately 140°F (60°C)

Flash Point: Method:

5°F (-15°C)

Specific Gravity:

Tag closed cup. 0.843 (H₂O=1)

Vapor Pressure @ 20LIC:

180mm Hg.

Vapor Density: Evaporation Rate: 2.0 (Air=1)

Melting Point:

>7 (Butyl Acetate=1) -95.6°C

Solubility in Water:

Soluble.

SECTION IV: FIRE AND EXPLOSION DATA

Flash Point:

5°F (-15°C)

Lower Flammable Limit:

2.6 (Volume % In air)

Upper Flammable Limit:

12.8 (Volume % in air)

OSHA Flammability Class:

Flammable Liquid IB.

Extinguishing Media:

Small Fire: Use carbon dioxide or dry chemical

Large Fire: Use alcohol foam.

Note:

Normal firefighting foams that are suitable for gasoline or hydrocarbon fires will break

down and will not extinguish acetone fires. Water spray will reduce the intensity of

the flames.

is nigner than that.

Unusual Fire and Explosion Hazards:

Nail Polish Remover is extremely flammable and its vapors form explosive mixtures with air.

Dangerous when exposed to heat, sparks, flame or oxidants.

Special Firefighting Precautions/Instructions:

Handle as a flammable liquid. Use water to keep fire-exposed tanks and containers cool. Do not enter fire area without proper personal protective equipment to include a self-contained breathing apparatus.

SECTION V: RECTIVITY DATA

Stability? Conditions to Avoid:

Normally stable. Keep away from heat, sparks and flame.

Incompatibility. Materials to Avoid:

Avoid strong oxidizing agents.

Hazardous Decomposition Products:

Carbon Monoxide, water vapor and unidentified organic compounds.

Hazardous Polymerization?

Updated September 11, 1998

Vi-Jon Regulatory Department

Hazardous polymerization will not occur.

SECTION VI: HEALTH HAZARD DATA

Potential Health Hazards:

Skin: Prolonged exposure to vapor irritates the skin. Repeated and prolonged contact of the liquid with the skin and cause dryness and erythema (inflammation).

Eves: Can cause irritation of the eyes and mucous membranes.

Inhalation: Vapor concentration of 2,500-3,000 ppm causes minor irritation of the eyes, nose and throat. Inhalation of higher concentration may cause headache, nausea, confusion, drowsiness, convulsions, and coma.

Ingestion: Ingestion of a toxic dose can cause gastoenteric irritation, narcosis and injury to the kidneys and liver.

Delayed Effects: Nail Polish Remover with DME is not known to produce chronic or cumulative systemic effects.

Carcinogenicity?

Eye:

NTP

IARC Status

OSHA

No ingredients listed in this section.

Medical Conditions Generally Aggravated by Exposure: pre-existing eye, skin, and respiratory disorders, and asthma.

SECTION VII: FIRST AID PROCEDURES

--- control of the co

In case of eye contact, immediately flush eyes with plenty of water for at least

15 minutes, keeping eyelids wide open. Get prompt medical attention.

Inhalation: If inhaled remove patient to fresh air. If not breathing give artificial respiration. If

breathing is difficult, oxygen can be given by a qualified operator. Get prompt

medical attention.

Ingestion: If swallowed, do not induce vomiting unless advised by a physician. Get prompt

medical attention.

SECTION VIII: PRECAUTIONS FOR SAFE HANDLING AND USE

In Case of Spill or Release:

Always wear the proper personal protective equipment. Eliminate all sources of ignition in the vicinity of the spill. Isolate the spill area and contain. Only trained personal fitted with the proper personal protective equipment should be allowed to enter the spill site. Terminate the leak immediately, if possible. Collect the spill in a waste container for disposal. Flush the spill area thoroughly with water. Spill and washings must be contained and prevented from entering a waterway.

Waste Disposal Method:

Dispose according to federal, state, and local regulations.

Updated September 11, 1998 Vi-Jon Regulatory Department Handling and Storage:

Do not store above 120°F (49°C). Keep away from sources of Ignition and oxidizing materials. Always use in a well ventilated area.

AEmpty≅ containers, must be assumed to be hazardous due to residual product.

Other Precautions:

Keep Away From Children!

SECTION IX: EXPOSURE CONTROLS

Engineering Controls:

Good ventilation is essential in areas where this product is handled to prevent the accumulation of explosive mixtures. Explosion-proof fans and electrical should be used in mechanical type ventilation systems.

Personal Protective Equipment:

Skin Protection:

Natural rubber, Butyl, or neoprene gloves and apron. Chemical resistant

safety shoes.

Eyes and Face:

Chemical safety goggles.

Other Protective Clothing or Equipment:

Eye Wash, safety shower, protective suit. Fire blankets. Warning signs.

Respiratory Protection:

No respiratory protection is required for concentrations below 750 ppm.

1,000-12,000 ppm-require NIOSH approved air purifying full face respirator with organic vapor canister.

12,500 ppm and above -requires NIOSH full face supplied air respirator operated in pressure demand or other positive pressure mode.

Escape-NIOSH approved air purifying, full face respirator with organic vapor canister or any escape type self-contained breathing apparatus.

Work/Hygienic Practices:

Following generally recognized safety practices and sound work methods should be used when handling this product in large or small quantities.

Notice

The information and recommendations contained in the Material Safety Data Sheet (MSDS) are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. The information and recommendations set forth herein (hereinafter "information") are presented in good faith and believed to be correct as of this date hereof.

The Cutex Company, however, makes no representation as to the completeness or accuracy thereof, and information is supplied upon the express condition that the persons receiving the information will

Updated September 11, 1998 Vi-Jon Regulatory Department be required to make their own determination as to its suitability for their purposes prior to use. In no event will The Cutex Company be responsible for any damages of any nature whatsnever resulting from the use of, reliance upon, or the misuse of this information.

No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, is made hereunder with respect to information or the product to which the information refers. The information as supplied herein is simply to be informative and intended solely to alert the user of the substance, which is the subject matter of this MSDS. The ultimate compliance with federal, state or local regulations concerning the use of this compound, or compliance with respect to products liability, rests solely upon the purchaser thereof.