



PRODUCT NAME Disc Brake Quiet

#-MSDS1015

PRODUCT-1015

(Page 1 of 2)

1. INGREDIENTS	CAS #	ACGIH TLV	OSHA PEL	OTHER LIMITS	%
Acetone	67-64-1	750 ppm	750 ppm		40-50
Ethyl Acetate	141-78-6	400 ppm	400 ppm		1-4
n-Hexane	110-54-3	50 ppm	50 ppm		0-2
Propane	74-98-6	NA	1000 ppm		10-20
Isobutane	75-28-5	NA	NA	1000ppm	10-20
Synthetic Resins	68648-53-3	NA	NA		13-20

2. PHYSICAL DATA : Includes propellant

Specific Gravity : 0.7

Vapor Pressure : ND

% Volatile : 85

Boiling Point : ND

Evaporation Rate : >1 butyl acetate=1

Freezing Point : ND

Vapor Density : 4.0

Appearance and Odor:

pH: NA

Light red in color- solvent odor.

Solubility : Negligible

3. FIRE AND EXPLOSION DATA

Flashpoint : -40 F Method : TCC

Flammable Limits : propellant LEL:1.8 UEL:12.0

Extinguishing Media : Use water fog, dry chemical or CO2

Unusual Hazards : Aerosol cans may explode if heated above 130 F.
Propellant is considered extremely flammable.

4. REACTIVITY AND STABILITY

Stability : Stable

Hazardous decomposition products

: Fire- Carbon dioxide and carbon monoxide

Materials to avoid : Strong oxidizers.

5. PROTECTION INFORMATION

Ventilation : Maintain vapor concentration below TLV. Use mechanical means if necessary.

Respiratory : Above TLV use self-contained breathing apparatus.

Gloves : Solvent resistant

Eye & Face : Safety glasses

Other Protective Equipment: Wear protective clothing if the exposure may be continuous.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME : Disc Brake Quiet # -MSDS1015
PRODUCTS-1015
MANUFACTURED BY : CRC INDUSTRIES, INC. PHONE (215) 674-4300
885 LOUIS DRIVE, WARMINSTER, PA. 18974

(Page 2 of 2)

6. HEALTH HAZARD DATA

Primary Routes of Entry : Inhalation, Skin

Signs and Symptoms of Exposure

1. Acute Overexposure:

May cause dizziness or narcosis. May cause irritation to eyes and upper respiratory tract. May cause defatting of the skin.

2. Chronic overexposure: Long term overexposures may cause lung, liver or kidney damage- may affect central nervous system

Medical Conditions Generally Aggravated by Exposure : ND

Chemical Listed as Carcinogen : No National Toxicology Program
or Potential Carcinogen : No IARC Monographs
: No OSHA

Emergency and First Aid Procedures : (If symptoms persist, call a physician)

1. **Inhalation** : Remove to fresh air. Apply artificial respiration if necessary.
2. **Eyes** : Flush with large amounts of water for 15 minutes.
3. **Skin** : Wash area with water.
4. **Ingestion** : DO NOT induce vomiting. Call a physician.

7. SPILL OR LEAK PROCEDURES

Precautions to be taken : Keep away from heat, sparks, or open flame. Store in Handling and Storage below 120 F.

Steps to be taken in case : Remove sources of ignition, ventilate area. Use Material is released or absorbant to soak up material and place in a spilled sealed container. Keep out of water supply.

Waste Disposal : All used and unused Product should be disposed of in conformance with local, state and federal regulations.

8. SPECIAL PRECAUTIONS AND USE DIRECTIONS :

When spraying more than one-half can continuously or more than one can consecutively, use NIOSH approved respirator.

9. NEPA HAZARD RATINGS Health:2 Flammability:4 Reactivity:0

10. SARA Information

This product contains the following chemicals that are subject to release reporting under Section 313 of SARA Title III.

Chemical Name	CAS-#	Percent
Acetone	67-64-1	40-50

PREPARED BY: Jen Brown ORIGINAL DATE or DATE OF REVISION: 12/17/93