E-403 01 00

MANUFACTURER'S NAME EMERGENCY TELEPHONE NO.

THE NOCO COMPANY (800) 424-9300

23300 Mercantile Rd.

Cleveland, OH 44122-5921

DATE OF PREPARATION INFORMATION TELEPHONE NO. (216) 464-8131 07-AUG-00

\_\_\_\_\_\_

Section I - PRODUCT IDENTIFICATION

PRODUCT NUMBER HMIS CODES

Health 1
Flammability 4
Reactivity 0 E - 403

PRODUCT NAME

NOCO\* Battery Cleaner

PRODUCT CLASS

Aerosol Cleaner

\_\_\_\_\_\_

Section II - HAZARDOUS INGREDIENTS

ACGIH OSHA INGREDIENT % by WT TLV PEL UNITS V.P. CAS No. 760.00 3 2500 1000 PPM Propane 74-98-6 7 800 800 PPM 760.00 Butane 106-97-8 pH - 7.0

\_\_\_\_\_\_

Section III - PHYSICAL DATA

PRODUCT WEIGHT 7.92 lb/gal 949 g/l

SPECIFIC GRAVITY 0.95

<0 - 213 F <-18 - 100 C BOILING POINT

MELTING POINT Not Available

VOLATILE VOLUME 97 %

Faster than ether EVAPORATION RATE VAPOR DENSITY Heavier than air

SOLUBILITY IN WATER N.A.

VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)

Volatile Weight 9.86 % Less Federally Exempt Solvents

HMIS - 1 4 0

\_\_\_\_\_\_

Section IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT LEL HET. 9.5 Propellant < 0 F 1.9

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Alcohol Foam UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

Continued on page 2

E-403 page 2

-----

## SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

\_\_\_\_\_\_

Section V - HEALTH HAZARD DATA

## ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

ACUTE Health Hazards

EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

EMERGENCY AND FIRST AID PROCEDURES

If INHALED: If affected, remove from exposure. Restore breathing.

Keep warm and quiet.

If on SKIN: Wash affected area thoroughly with soap and water.

Remove contaminated clothing and launder before re-use.

If in EYES: Flush eyes with large amounts of water for 15 minutes.

Get medical attention.

If SWALLOWED: Get medical attention.

CHRONIC Health Hazards

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

\_\_\_\_\_\_

Section VI - REACTIVITY DATA

STABILITY - Stable CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

\_\_\_\_\_\_

Section VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

Continued on page 3

E-403 page 3

\_\_\_\_\_\_

## WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

\_\_\_\_\_

Section VIII - PROTECTION INFORMATION

## PRECAUTIONS TO BE TAKEN IN USE

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108. RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II. PROTECTIVE GLOVES

None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

\_\_\_\_\_

Section IX - PRECAUTIONS

DOL STORAGE CATEGORY

1 A

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

\_\_\_\_\_

Section X - OTHER REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No. CHEMICAL/COMPOUND % by WT % Element

No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

E-403 page 4

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.