



# SAFETY DATA SHEET

Revision Date 13-Apr-2016

Version 2

## 1. IDENTIFICATION

### Product identifier

**Product Name** 116DA SILICONE SPRAY LUBRICANT 10.25OZ AE

### Other means of identification

**Product Code** 80070

**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** Flammable Aerosol Lubricant

**Uses advised against** No information available

### Details of the supplier of the safety data sheet

#### Manufacturer Address

ITW Permatex  
6875 Parkland Blvd.  
Solon, OH 44139 USA

#### Distributor

ITW Permatex Canada  
35 Brownridge Road, Unit 1  
Halton Hills, ON Canada L7G 0C6  
Telephone: (800) 924-6994

**Company Phone Number** 1-87-Permatex

(877) 376-2839

**24 Hour Emergency Phone Number** Chem-Tel: 800-255-3924

International Emergency:

00+1+ 813-248-0585

Contract Number: MIS0003453

**E-mail address** mail@permatex.com

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Liquefied gas

### Label elements

#### Emergency Overview

#### **Danger**

May be fatal if swallowed and enters airways  
Extremely flammable aerosol  
Contains gas under pressure; may explode if heated



**Appearance** White

**Physical state** Liquid Flammable Aerosol

**Odor** Mild

**Precautionary Statements - Prevention**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
Do not spray on an open flame or other ignition source  
Pressurized container: Do not pierce or burn, even after use

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
Do NOT induce vomiting

**Precautionary Statements - Storage**

Store locked up  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Other Information**

- The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0.1 % w/w 1,3-butadiene (EINECS No. 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the S-phrases (2-)9-16 (Table 3.2) should apply. This note applies only to certain complex oil-derived substances in Part 3

Unknown acute toxicity                      2.5 % of the mixture consists of ingredient(s) of unknown toxicity

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**substance(s)**

Chemical Name	CAS No	Weight-%	Trade Secret
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	10 - 30	*
BUTANE	106-97-8	10 - 30	*
PROPANE	74-98-6	3 - 7	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES**

**Description of first aid measures**

**General advice**                      Get medical advice/attention if you feel unwell.

**Eye contact**                        IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**Skin contact**                        IF ON SKIN: Wash skin with soap and water. If skin irritation persists, call a physician. Wash contaminated clothing before reuse.

---

<b>Inhalation</b>	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
<b>Ingestion</b>	IF SWALLOWED: Call a physician or poison control center immediately. Do NOT induce vomiting.
<b>Self-protection of the first aider</b>	Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.
<b><u>Most important symptoms and effects, both acute and delayed</u></b>	
<b>Symptoms</b>	See section 2 for more information.
<b><u>Indication of any immediate medical attention and special treatment needed</u></b>	
<b>Note to physicians</b>	Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

### **Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>), Dry chemical, Foam

### **Unsuitable extinguishing media**

None.

### **Specific hazards arising from the chemical**

Extremely flammable. Heating causes rise in pressure with risk of bursting.

### **Explosion data**

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

### **Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### **Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin. Use personal protective equipment as required.

### **Environmental precautions**

**Environmental precautions** Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological Information.

### **Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

## 7. HANDLING AND STORAGE

### **Precautions for safe handling**

**Advice on safe handling** Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Contents under pressure. Do not puncture or incinerate cans.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store locked up.

**Incompatible materials** Strong oxidizing agents

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
BUTANE 106-97-8	STEL: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>
PROPANE 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup>	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Other Information** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Appropriate engineering controls**

**Engineering Controls** Showers  
Eyewash stations  
Ventilation systems

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

**Respiratory protection** Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

**Physical state** Liquid; Flammable Aerosol  
**Appearance** White  
**Odor** Mild  
**Odor threshold** No information available

Property	Values	Remarks • Method
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	> 38 °C / >100 °F	

<b>Flash point</b>	No information available	Gives a flame projection at full valve opening or flashback at any degree of valve opening
<b>Evaporation rate</b>	< 1	Butyl acetate = 1
<b>Flammability (solid, gas)</b>	No information available	
<b>Flammability Limit in Air</b>		
<b>Upper flammability limit:</b>	No information available	
<b>Lower flammability limit:</b>	No information available	
<b>Vapor pressure</b>	No information available	
<b>Vapor density</b>	>1	Air = 1
<b>Relative density</b>	0.94	
<b>Water solubility</b>	No information available	
<b>Solubility in other solvents</b>	No information available	
<b>Partition coefficient</b>	No information available	
<b>Autoignition temperature</b>	No information available	
<b>Decomposition temperature</b>	No information available	
<b>Kinematic viscosity</b>	No information available	
<b>Dynamic viscosity</b>	No information available	
<b>Explosive properties</b>	No information available	
<b>Oxidizing properties</b>	No information available	

**Other Information**

<b>Softening point</b>	No information available
<b>Molecular weight</b>	No information available
<b>VOC Content (%)</b>	20%
<b>Density</b>	No information available
<b>Bulk density</b>	No information available

**10. STABILITY AND REACTIVITY**

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks. Temperatures >50 °C / 122 °F.

**Incompatible materials**

Strong oxidizing agents

**Hazardous Decomposition Products**

Carbon oxides

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

<b>Inhalation</b>	May cause irritation of respiratory tract.
<b>Eye contact</b>	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
<b>Skin contact</b>	May cause skin irritation and/or dermatitis.
<b>Ingestion</b>	Harmful if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT 64742-47-8	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.2 mg/L ( Rat ) 4 h
BUTANE 106-97-8	-	-	= 658 g/m <sup>3</sup> ( Rat ) 4 h
PROPANE 74-98-6	-	-	= 658 mg/L ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** No information available.

**Target Organ Effects** Central nervous system.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 22274 mg/kg

ATEmix (dermal) 7700 mg/kg

ATEmix (inhalation-gas) 1337916 mg/l

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

78.5 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT 64742-47-8	-	45: 96 h Pimephales promelas mg/L LC50 flow-through 2.2: 96 h Lepomis macrochirus mg/L LC50 static 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static	4720: 96 h Den-dronereides heteropoda mg/L LC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility**

No information available.

Chemical Name	Partition coefficient
BUTANE 106-97-8	2.89
PROPANE 74-98-6	2.3

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal of wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Do not reuse container.  
US EPA Waste Number D001

#### 14. TRANSPORT INFORMATION

##### DOT

UN/ID no 1950  
Proper shipping name: Aerosols, Limited Quantity (LQ)  
Hazard Class 2.1  
Emergency Response Guide Number 126

##### IATA

UN/ID no ID 8000  
Proper shipping name: Consumer commodity  
Hazard Class 9  
ERG Code 9L

##### IMDG

UN/ID no 1950  
Proper shipping name: Aerosols, Limited Quantity (LQ)  
Hazard Class 2.1  
EmS-No F-D, S-U

#### 15. REGULATORY INFORMATION

##### International Inventories

TSCA Complies  
DSL/NDSL Complies  
EINECS/ELINCS Not Listed.  
ENCS Complies  
IECSC Complies  
KECL Complies  
PICCS Complies  
AICS Complies

##### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List  
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
ENCS - Japan Existing and New Chemical Substances  
IECSC - China Inventory of Existing Chemical Substances  
KECL - Korean Existing and Evaluated Chemical Substances  
PICCS - Philippines Inventory of Chemicals and Chemical Substances  
AICS - Australian Inventory of Chemical Substances

##### US Federal Regulations

##### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

##### SARA 311/312 Hazard Categories

Acute health hazard Yes  
Chronic Health Hazard No  
Fire hazard Yes

**Sudden release of pressure hazard** No  
**Reactive Hazard** No

**CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

**US State Regulations**

**California Proposition 65**

This product does not contain any Proposition 65 chemicals

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
BUTANE 106-97-8	X	X	X
PROPANE 74-98-6	X	X	X

**U.S. EPA Label Information**

**EPA Pesticide Registration Number** Not applicable

**WHMIS Hazard Class**

A Compressed gases, B5 - Flammable aerosol, D2B - Toxic materials

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

<b>NFPA</b>	<b>Health hazards</b> 2	<b>Flammability</b> 3	<b>Instability</b> 0	-
<b>HMIS</b>	<b>Health hazards</b> 2	<b>Flammability</b> 3	<b>Physical hazards</b> 0	<b>Personal protection</b> B

NFPA (National Fire Protection Association)  
HMIS (Hazardous Material Information System)

**Revision Date** 13-Apr-2016

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**