

133



Welcome ridge auto parts

Current Order: New Order

Current Store: NAPA AUTO PARTS-MAIN STORE

Store Address: 2020 W. COLISEUM BLVD

**Part Searches**

[Job Type](#)

[Category](#)

[Back to Previous Page](#)

[Subcategory](#)

[NAPA Part Number](#)

[Interchange](#)

[Keyword](#)

[Exhaust](#)

MATERIAL SAFETY DATA SHEET  
 The Valvoline Company  
 Date Prepared: 01/14/02  
 Date Printed: 12/01/04  
 MSDS No: 503.0236406-001.012  
 PYROIL SILICONE SPRAY

Page 001

8300

[Vehicle Selection](#)

[Last Search Result](#)

**Orders**

[Current Order](#)

[New Order](#)

[Saved Orders](#)

[New Stock Order](#)

[Stock Orders](#)

[Submitted Orders](#)

[Help](#)

[Welcome](#)

[Vehicle Information](#)

[Log Out](#)

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity

Product Name: PYROIL SILICONE SPRAY

SAP Material No: NM8300

General or Generic ID: SILICONE SOLUTION

Company

Telephone Numbers

The Valvoline Company

Emergency: 1-800-274-5263

P.O. Box 14000

Lexington, KY 40512

Information: 1-859-357-7206

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS Number	% (by weight)
HEPTANE	142-82-5	87.0- 97.0
CARBON DIOXIDE	124-38-9	0.0- 10.0
SILICONE	Trade Secret	0.0- 8.0

3. HAZARDS IDENTIFICATION

Potential Health Effects

Eye

May cause mild eye irritation.

Skin

May cause mild skin irritation. Prolonged or repeated contact may dry and crack the skin.

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 002

Date Prepared: 01/14/02

Date Printed: 12/01/04

MSDS No: 503.0236406-001.012

PYROIL SILICONE SPRAY

Inhalation

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful.

Symptoms of Exposure

Stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), and death.

Target Organ Effects

Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory

animals, and may aggravate preexisting disorders of these organs in humans: effects on hearing, central nervous system damage, Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans, and may aggravate preexisting disorders of these organs: central nervous system effects.

Developmental Information

No data

Cancer Information

No data

Other Health Effects

No data

Primary Route(s) of Entry

Inhalation, Skin contact.

---

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 003

Date Prepared: 01/14/02

Date Printed: 12/01/04

MSDS No: 503.0236406-001.012

PYROIL SILICONE SPRAY

---

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Swallowing

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, immediately move individual away from exposure and into fresh air. Seek immediate medical attention; keep person warm and quiet. If person is not breathing, begin artificial respiration. If breathing is difficult, administer oxygen.

Note to Physicians

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 3 - Swallowing) when deciding whether to induce vomiting. Preexisting disorders of the following organs ( or organ systems) may be aggravated by exposure to this material: skin.

---

5. FIRE FIGHTING MEASURES

Flash Point

Not applicable

Explosive Limit

(for component) Lower 1.1 Upper 10.0 %

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 004

Date Prepared: 01/14/02

Date Printed: 12/01/04

MSDS No: 503.0236406-001.012

PYROIL SILICONE SPRAY

---

Autoignition Temperature

No data

Hazardous Products of Combustion

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Fire and Explosion Hazards

Material is highly volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by

pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point.

Extinguishing Media

regular foam, carbon dioxide, dry chemical.

Fire Fighting Instructions

Water may be used to keep fire-exposed containers cool until fire is out. Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Refer to the personal protective equipment section of this MSDS.

NFPA Rating

Health - 1, Flammability - 3, Reactivity - 0

---

6. ACCIDENTAL RELEASE MEASURES

Small Spill

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

---

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 005

Date Prepared: 01/14/02

Date Printed: 12/01/04

MSDS No: 503.0236406-001.012

PYROIL SILICONE SPRAY

---

Large Spill

Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

---

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Storage

Not applicable

---

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

Skin Protection

Wear resistant gloves such as: nitrile rubber, To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

---

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 006

Date Prepared: 01/14/02

Date Printed: 12/01/04

MSDS No: 503.0236406-001.012

PYROIL SILICONE SPRAY

---

Respiratory Protections

If workplace exposure limit(s) of product or any component is exceeded (See Exposure Guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (consult your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure. Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Exposure Guidelines

Component

-----  
 HEPTANE (142-82-5)  
 OSHA VPEL 400.000 ppm - TWA  
 OSHA VPEL 500.000 ppm - STEL  
 ACGIH TLV 400.000 ppm - TWA  
 ACGIH TLV 500.000 ppm - STEL  
 CARBON DIOXIDE (124-38-9)  
 OSHA VPEL 10000.000 ppm - TWA  
 OSHA VPEL 30000.000 ppm - STEL  
 ACGIH TLV 5000.000 ppm - TWA  
 ACGIH TLV 30000.000 ppm - STEL  
 SILICONE  
 No exposure limits established

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point

(for component) 200.0 F (93.3 C) @ 760 mmHg

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 007

Date Prepared: 01/14/02

Date Printed: 12/01/04

MSDS No: 503.0236406-001.012

PYROIL SILICONE SPRAY

Vapor Pressure

(for component) 40.000 mmHg @ 68.00 F

Specific Vapor Density

> 1.000 @ AIR=1

Specific Gravity

.700 - .710 @ 77.00 F

Liquid Density

5.940 lbs/gal @ 77.00 F

.710 kg/l @ 25.00 C

Percent Volatiles (Including Water)

No data

Evaporation Rate

No data

Appearance

No data

State

LIQUID

Physical Form

AEROSOL

Color

No data

Odor

No data

pH

Not applicable

MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 008

Date Prepared: 01/14/02

Date Printed: 12/01/04

MSDS No: 503.0236406-001.012

PYROIL SILICONE SPRAY

Flame Propagation

> 18.000 in

10. STABILITY AND REACTIVITY

Hazardous Polymerization

Product will not undergo hazardous polymerization.

Hazardous Decomposition

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

Chemical Stability

Stable.

## Incompatibility

Avoid contact with: strong oxidizing agents.

---

11. TOXICOLOGICAL INFORMATION

No data

---

12. ECOLOGICAL INFORMATION

No data

---

13. DISPOSAL CONSIDERATION

Waste Management Information

Dispose of in accordance with all applicable local, state and federal regulations.

## MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 009

Date Prepared: 01/14/02

Date Printed: 12/01/04

MSDS No: 503.0236406-001.012

PYROIL SILICONE SPRAY

---

14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101

DOT Description:

AEROSOLS, 2.1, UN 1950

Container/Mode:

CASES/SURFACE - NO EXCEPTIONS

NOS Component:

None

RQ (Reportable Quantity) - 49 CFR 172.101

Not applicable

---

15. REGULATORY INFORMATION

US Federal Regulations

CERCLA RQ - 40 CFR 302.4

None

SARA 302 Components - 40 CFR 355 Appendix A

None

Section 311/312 Hazard Class - 40 CFR 370.2

Immediate(X) Delayed(X) Fire(X) Reactive( ) Sudden

Release of Pressure( )

SARA 313 Components - 40 CFR 372.65

None

International Regulations

Inventory Status

Not determined

## MATERIAL SAFETY DATA SHEET

The Valvoline Company

Page 010

Date Prepared: 01/14/02

Date Printed: 12/01/04

MSDS No: 503.0236406-001.012

PYROIL SILICONE SPRAY

---

State and Local Regulations

California Proposition 65

None

New Jersey RTK Label Information

N-HEPTANE

142-82-5

CARBON DIOXIDE

124-38-9

Pennsylvania RTK Label Information

HEPTANE (N-)

142-82-5

CARBON DIOXIDE

124-38-9

---

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

circumstances.

Mac's Silicone Spray

=====

MATERIAL SAFETY DATA SHEET

Effective Date: 2-26-02

Revision Date: none

Mac's Silicone Spray

=====

Section 1 - Product and Company Identification

PRODUCT NAME: Mac's Silicone Spray

MANUFACTURER'S NAME:  
 Technical Chemical Corp.  
 P O BOX 139  
 CLEBURNE , TX 76033

EMERGENCY TELEPHONE NUMBER  
 (817)645-6088

MISCELLANEOUS INFORMATION

=====

MATERIAL SAFETY DATA SHEET

Effective Date: 2-26-02

Revision Date: none

Mac's Silicone Spray

=====

Section 1 - Product and Company Identification - Continued

MATERIAL SAFETY DATA SHEET

Trade Name: Johnsens Silicone Spray

MSDS NO. 4603

Revision Date: 02/26/2002

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name: Johnsens Silicone Spray

Chemical Family: SILICONE POLYMER SOLUTION

Synonyms: None

Emergency Telephone (24 hr.): 24-Hour Emergency Information: CHEMTREC (800) 424-9300

Supplier:

Technical Chemical Company, P.O. Box 139, Cleburne, Texas 76033

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient/CAS No.

wt. %

OSHA PEL

TWA

OSHA PEL

Ceiling Limits

ACGIH TLV

TWA

ACGIH TLW

STEL

Heptane

142-82-5

25-50 500 ppm: 2000

mg/m3

None Established 400 ppm: 1640 mg/m3 500 ppm

Methyl Hexanes

None

40-50 None Established None Established None Established None Established

Polydimethylsiloxane

63148-62-9

10-20 None Established None Established None Established None Established

Dimethyl Pentanes

None

5-10 None Established None Established None Established None Established

Dimethyl Cyclopentanes

None

4-7 None Established None Established None Established None Established

Propane

74-98-6

2-6 1000 ppm Not Known 2500 ppm Not Known

Toluene

108-88-3

1-4 100 ppm 150 ppm 100 ppm 150 ppm

Iso-Butane  
75-28-5

1-4 None Established None Established None Established None Established  
This product does not contain Normal Hexane (N-Hexane).

### 3. HAZARDS IDENTIFICATION

Emergency Overview: Warning: Extremely Flammable. Content under pressure.  
This material is an eye and skin irritant. Keep away from heat,  
sparks and flame. Gross inhalation overexposure may cause: Central nervous  
system depression with dizziness,

---

#### MATERIAL SAFETY DATA SHEET

Effective Date: 2-26-02

Revision Date: none

Mac's Silicone Spray

---

#### Section 1 - Product and Company Identification - Continued

confusion, incoordination, drowsiness or unconsciousness or death. Causes  
respiratory irritation. This product contains  
dimethylpolysiloxane which can generate small amounts of formaldehyde as a  
byproduct of oxidative thermal  
decomposition beginning at approximately 150 C (300 F). Exposure to  
formaldehyde can cause adverse effects such as  
skin and respiratory sensitization and eye and throat irritation.  
Formaldehyde is a potential cancer hazard. Use good  
industrial hygiene practices to evaluate and control exposure to  
formaldehyde when warranted by conditions of use. This  
material is readily absorbed through the skin in liquid or vapor phase.

#### 4. FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eyes with plenty of water  
for at least 15 minutes and get medical attention if irritation  
persists.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician  
immediately. Never give anything by mouth to an unconscious  
person. Get medical attention! If vomiting occurs, keep head lower than hips  
to prevent aspiration.

Inhalation: If inhaled, remove to fresh air. If not breathing give  
artificial respiration, preferably mouth-to-mouth. If breathing is difficult  
give oxygen. Get medical attention.

Skin Contact: Wash with soap and water for 15 minutes. If irritation  
persists or signs of toxicity occur, seek medical attention. Remove  
contaminated clothing and launder before reuse.

#### 5. FIRE FIGHTING MEASURES

Flammable Properties

Flash Point F(C): 15 F (Lowest Component)

Flash Point Method: TAG Closed Cup

Flammable Limits in Air - Lower (%): 1.2% (Lowest Component)

Page 1 of 4

Trade Name: Johnsens Silicone Spray MSDS NO. 4603

Flammable Limits in Air - Upper (%): 6.7% (Lowest Component)

Autoignition Temperature F(C): Not Determined

Extinguishing Media: Dry chemical. Carbon dioxide. Use water spray to keep  
containers cool that are exposed to heat or  
flames. Foam.

Protection Of Fire-Fighters:

Special Fire-Fighting Procedures: Wear approved positive-pressure  
self-contained breathing apparatus and protective clothing. Vapor  
may cause flash fire.

Hazardous Combustion Products: Carbon Dioxide. Carbon Monoxide.

Aerosol Comments: NFPA Level 3 Aerosol

#### 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear appropriate protective clothing and equipment to  
prevent skin and eye contact.

Spill Procedures: Contain any liquid from leaking containers. Avoid all  
sources of ignition; heat, sparks and open flames.

Do not puncture or incinerate container. Contents under pressure. Wear  
proper protective equipment as specified in  
the protective equipment section. Remove sources of ignition. Leaking  
containers should be removed to an isolated,  
well-ventilated area and transferred to other suitable containers. Wipe,  
scrape, or soak up in an inert material and put  
in a container intended for flammable materials for disposal.

---

MATERIAL SAFETY DATA SHEET

Effective Date: 2-26-02  
Mac's Silicone Spray

Revision Date: none

=====  
Section 1 - Product and Company Identification - Continued

Environmental Precautions: Do not allow to enter sanitary drains, sewer or surface and subsurface waters. Keep out of lakes, ponds or streams.

7. HANDLING AND STORAGE

Handling and  
Storage:

Caution: Contents under pressure. Keep away from heat and open flame. Use only in a well ventilated area. Avoid breathing vapors, if exposed to high vapor concentration, leave area at once. Avoid contact with skin and eyes. Do not puncture, incinerate or store above 120 F. Exposure to high temperatures may cause bursting. DO NOT store in the passenger compartment of an automobile.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Use in a well ventilated area. Local exhaust ventilation as necessary to maintain exposures to within applicable limits.

Eyes: Chemical goggles; also wear a face shield if splashing hazard exists.  
Skin Protection: Avoid skin contact. Wear protective clothing and gloves.  
Respiratory Protection: Do not breathe mist or vapor. Use in a well ventilated area. Appropriate respiratory protection shall be worn when applied engineering controls are not adequate to protect against inhalation exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Colorless to pale yellow liquid

Odor: MILD pH Value: Not Determined

Vapor Pressure: 2.3 psia @ 100 F Vapor Density (Air=1): 3.5 Approximate

Boiling Point (F): 195 F (Lowest Component) Melting/Freezing Point: Not determined.

Solubility in Water: NEGLIGIBLE Bulk Density at 20C: Not Determined

Molecular Weight: Mixture Evaporation Rate: >1

Viscosity: Not Determined. Specific Gravity (H2O=1): .69 - .79 @ 60 F

VOC Content(%): Not determined. Decomposition Temperature: Not Determined

10. STABILITY AND REACTIVITY

Chemical Stability: STABLE.

Conditions to Avoid: Keep away from heat, sparks and flame. Avoid any source of ignition. Do not expose to heat or store at temperatures above 120f.

Materials to Avoid: Contact with oxidizing agents. Strong bases. Strong acids.

Hazardous Decomposition Products: Carbon monoxide. Silica. Formaldehyde is a byproduct of oxidative thermal decomposition.

Hazardous Polymerization: WILL NOT OCCUR

11. TOXICOLOGICAL INFORMATION

Toxicological Data:

Ingredient/CAS No.

wt. %

Route Species Dose

Heptane

142-82-5

25-50 Inhalation Rats LC50 103 gm/m3/4H

Methyl Hexanes

None

40-50 NA NA Not known.

Polydimethylsiloxane

63148-62-9

=====  
MATERIAL SAFETY DATA SHEET

Effective Date: 2-26-02

Revision Date: none

Mac's Silicone Spray

=====  
Section 1 - Product and Company Identification - Continued

10-20 Oral Rats LD50 >17 gm/kg

Dimethyl Pentanes

None

5-10 NA NA Not known.

Dimethyl Cyclopentanes

None

4-7 NA NA Not known.



Propane  
74-98-6  
2-6 NA NA Not known.  
Page 2 of 4  
Trade Name: Johnsens Silicone Spray MSDS NO. 4603  
Toluene  
108-88-3  
1-4 Inhalation Rats LC50 49 gm/m3/4H  
Iso-Butane  
75-28-5  
1-4 Inhalation Rats LC50 57 pph/15M  
Carcinogenicity:  
Ingredient/CAS No.  
wt. %  
IARC NTP OSHA  
Heptane  
142-82-5  
25-50 Not Listed Not Listed Not Listed  
Methyl Hexanes  
None  
40-50 Not Listed Not Listed Not Listed  
Polydimethylsiloxane  
63148-62-9  
10-20 Not Listed Not Listed Not Listed  
Dimethyl Pentanes  
None  
5-10 Not Listed Not Listed Not Listed  
Dimethyl Cyclopentanes  
None  
4-7 Not Listed Not Listed Not Listed  
Propane  
74-98-6  
2-6 Not Listed Not Listed Not Listed  
Toluene  
108-88-3  
1-4 Group 3 (not classifiable) Not Listed Not Listed  
Iso-Butane  
75-28-5  
1-4 Not Listed Not Listed Not Listed  
12. ECOLOGICAL INFORMATION  
Ecological testing has not been conducted on this product.  
13. DISPOSAL CONSIDERATION  
Waste Classification: Residues and spilled material are hazardous waste due to ignitability.  
Waste Management: Not determined.  
Disposal should be made in accordance with federal, state and local regulations.  
14. TRANSPORTATION INFORMATION

=====

MATERIAL SAFETY DATA SHEET  
Effective Date: 2-26-02  
Mac's Silicone Spray

Revision Date: none

=====

Section 1 - Product and Company Identification - Continued

U.S. DOT:  
Proper Shipping Name: ORM-D CONSUMER COMMODITY  
Hazard Class: ORM-D  
UN/NA Number: Not Applicable  
DOT Packing Group: Not Applicable  
IMDG:  
Proper Shipping Name: Aerosols (Limited Quantity)  
Hazard Class: 2.1  
Hazard Subclass: Not determined.  
UN No.: UN1950  
Packing Group: PG II  
Marine Pollutant: No  
15. REGULATORY INFORMATION  
US Federal Regulations:  
Page 3 of 4  
Trade Name: Johnsens Silicone Spray MSDS NO. 4603  
Ingredient/CAS No.  
wt. %  
SARA 313 SARA 302 RQ TPQ

Heptane  
 142-82-5  
 25-50 Not Listed Not Listed NA NA  
 Methyl Hexanes  
 None  
 40-50 Not Known Not Known NA NA  
 Polydimethylsiloxane  
 63148-62-9  
 10-20 Not Listed Not Listed NA NA  
 Dimethyl Pentanes  
 None  
 5-10 Not Known Not Known NA NA  
 Dimethyl Cyclopentanes  
 None  
 4-7 Not Known Not Known NA NA  
 Propane  
 74-98-6  
 2-6 Not Listed Not Listed NA NA  
 Toluene  
 108-88-3  
 1-4 Listed Not Listed 1000 lbs. NA  
 Iso-Butane  
 75-28-5  
 1-4 Not Listed Not Listed NA NA  
 Hazardous per OSHA 29 CFR 1910.1200  
 SARA 311/312 Hazard Categories: Not Determined.  
 State Regulations:  
 Ingredient/CAS No.  
 wt. %  
 California Prop. 65  
 Cancer list  
 California Prop. 65  
 Developmental  
 Toxicity  
 California Prop. 65  
 Reproductive Female

=====

MATERIAL SAFETY DATA SHEET

Effective Date: 2-26-02

Revision Date: none

Mac's Silicone Spray

=====

Section 1 - Product and Company Identification - Continued

California Prop. 65  
 Reproductive Male  
 Heptane  
 142-82-5  
 25-50 Not Listed Not Listed Not Listed Not Listed  
 Methyl Hexanes  
 None  
 40-50 Not Listed Not Listed Not Listed Not Listed  
 Polydimethylsiloxane  
 63148-62-9  
 10-20 Not Listed Not Listed Not Listed Not Listed  
 Dimethyl Pentanes  
 None  
 5-10 Not Listed Not Listed Not Listed Not Listed  
 Dimethyl Cyclopentanes  
 None  
 4-7 Not Listed Not Listed Not Listed Not Listed  
 Propane  
 74-98-6  
 2-6 Not Listed Not Listed Not Listed Not Listed  
 Toluene  
 108-88-3  
 1-4 Not Listed Listed, Developmental  
 toxicity:initial date  
 1/1/91  
 Not Listed Not Listed  
 Iso-Butane  
 75-28-5  
 1-4 Not Listed Not Listed Not Listed Not Listed  
 U.S. TSCA: The components of this product are listed on the TSCA Inventory.  
 16. OTHER INFORMATION

General Notes: Do not allow undiluted material or large quantities to reach groundwater, bodies of water or sewer system.

Disclaimer:

The information and recommendations contained herein are based upon tests believed to be reliable. However, Technical Chemical Company does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. Technical Chemical Company assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

Page 4 of 4

[Back to Previous Page](#)

US 060106

